

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 12/31/2014

Revision date: 12/31/2014

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SERVICE PRO INTAKE VALVE CLEANER
Product code : SP2313

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel System cleaner.

1.3. Details of the supplier of the safety data sheet

The Penray Companies, Inc.
440 Denniston Ct.
Wheeling, IL 60090
T (800) 373-6729

Manufactured for:
AIOD
P.O. Box 1861
Montrose, CO 81402-1861
970-249-6336

1.4. Emergency telephone number

Emergency number : (800) 373-6729
CHEMTREC (800) 424-9300
CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquid 2
Skin irritation 2
Carcinogenicity 2
Specific target organ toxicity - Single exposure 3
Aspiration hazard 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02



GHS07



GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

4 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Kerosine, petroleum	(CAS No) 8008-20-6	60 - 100	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Poly olef in alky l phenol alky l amine	Proprietary	1 - 2	Skin Irrit. 2 Eye Irrit. 2A
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	0.5 - 1.5	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Naphthalene	(CAS No) 91-20-3	< 0.5	Acute Tox. 4 (Oral) Carc. 2
Cumene	(CAS No) 98-82-8	< 0.1	Flam. Liq. 3 Acute Tox. 4 (Oral) Carc. 2 STOT SE 3 Asp. Tox. 1
Ethylbenzene	(CAS No) 100-41-4	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2
Toluene	(CAS No) 108-88-3	< 0.1	Flam. Liq. 2 Skin Irrit. 2 Repr. 2 (developmental) STOT SE 3 STOT RE 2 Asp. Tox. 1
Benzene	(CAS No) 71-43-2	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Eye Irrit. 2A Muta. 1B Carc. 1A STOT RE 1 Asp. Tox. 1
Furan	(CAS No) 110-00-9	< 0.1	Flam. Liq. 1 Acute Tox. 4 (Oral) Acute Tox. 3 (Inhalation) Skin Irrit. 2 Muta. 2 Carc. 1B STOT RE 2
Propylene oxide	(CAS No) 75-56-9	< 0.1	Flam. Liq. 1 Acute Tox. 3 (Inhalation) Acute Tox. 4 (Oral, Dermal) Eye Irrit. 2A Muta. 1B Carc. 2 STOT SE 3
Acetaldehyde	(CAS No) 75-07-0	< 0.1	Flam. Liq. 1 Eye Irrit. 2A Carc. 2 STOT SE 3

* The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Kerosine, petroleum (8008-20-6)

USA ACGIH	ACGIH TWA (mg/m ³)	200 mg/m ³
-----------	--------------------------------	-----------------------

Polyolefin alkyl phenol alkyl amine (Proprietary)

ACGIH	Not applicable
-------	----------------

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Polyolefin alkyl phenol alkyl amine (Proprietary)

OSHA	Not applicable
------	----------------

Benzene, 1,2,4-trimethyl- (95-63-6)

ACGIH	Not applicable
-------	----------------

OSHA	Not applicable
------	----------------

Naphthalene (91-20-3)

USA ACGIH	ACGIH TWA (ppm)	10 ppm
-----------	-----------------	--------

USA ACGIH	ACGIH STEL (ppm)	15 ppm
-----------	------------------	--------

USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m ³
----------	-------------------------------------	----------------------

USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm
----------	----------------------	--------

Cumene (98-82-8)

USA ACGIH	ACGIH TWA (ppm)	50 ppm
-----------	-----------------	--------

USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
----------	-------------------------------------	-----------------------

USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
----------	----------------------	--------

Ethylbenzene (100-41-4)

USA ACGIH	ACGIH TWA (ppm)	20 ppm
-----------	-----------------	--------

USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
----------	-------------------------------------	-----------------------

USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
----------	----------------------	---------

Toluene (108-88-3)

USA ACGIH	ACGIH TWA (ppm)	20 ppm
-----------	-----------------	--------

USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
----------	----------------------	---------

USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
----------	--------------------------	---------

Benzene (71-43-2)

USA ACGIH	ACGIH TWA (ppm)	0.5 ppm
-----------	-----------------	---------

USA ACGIH	ACGIH STEL (ppm)	2.5 ppm
-----------	------------------	---------

USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
----------	----------------------	-------

USA OSHA	OSHA PEL (STEL) (ppm)	5 ppm
----------	-----------------------	-------

USA OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm
----------	--------------------------	--------

Furan (110-00-9)

ACGIH	Not applicable
-------	----------------

OSHA	Not applicable
------	----------------

Propylene oxide (75-56-9)

USA ACGIH	ACGIH TWA (ppm)	2 ppm
-----------	-----------------	-------

USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
----------	-------------------------------------	-----------------------

USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
----------	----------------------	---------

Acetaldehyde (75-07-0)

USA OSHA	OSHA PEL (TWA) (mg/m ³)	360 mg/m ³
----------	-------------------------------------	-----------------------

USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
----------	----------------------	---------

8.2. Exposure controls

- | | |
|----------------------------------|--|
| Appropriate engineering controls | : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. |
| Personal protective equipment | : Avoid all unnecessary exposure. |
| Hand protection | : Wear chemically resistant protective gloves. |

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear
Color	: Amber
Odor	: Petroleum odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 22 °C (71 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.864 - 0.869
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

SP2313	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	No data available

Kerosine, petroleum (8008-20-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h

Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	18 g/m ³ /4h

Naphthalene (91-20-3)	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	> 20 g/kg

Cumene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	>3160 mg/kg
LC50 inhalation rat	39000 mg/m ³ /4h

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat	17.2 mg/l/4h

Toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	8390 mg/kg
LD50 dermal rat	12124 mg/kg
LC50 inhalation rat	28.1 mg/l/4h

Benzene (71-43-2)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	> 9.4 ml/kg
LC50 inhalation rat	13050-14380 ppm/4h

Furan (110-00-9)	
LC50 inhalation rat	3398 ppm/1h

Propylene oxide (75-56-9)	
LD50 oral rat	520 mg/kg
LD50 dermal rabbit	1244 mg/kg
LC50 inhalation rat	4000 ppm/4h

Acetaldehyde (75-07-0)	
LD50 oral rat	1930 mg/kg
LC50 inhalation rat	13300 ppm/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.
Germ cell mutagenicity : Based on available data, the classification criteria are not met.
Carcinogenicity : Suspected of causing cancer.

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Naphthalene (91-20-3)	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Benzene (71-43-2)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens
	In OSHA Specifically Regulated Carcinogen list
Furan (110-00-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Propylene oxide (75-56-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Acetaldehyde (75-07-0)	
IARC group	1 - Carcinogenic to humans (associated with consumption of alcoholic beverages), 2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

SP2313	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

SP2313	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
- Additional information : Handle empty containers with care because residual vapors are flammable.

SECTION 14: Transport information

In accordance with DOT

- UN-No.(DOT) : UN1993
- Proper Shipping Name (DOT) : Flammable liquids, n.o.s. (Petroleum, Benzene, 1,2,4-trimethyl-)
- Department of Transportation (DOT) Hazard Classes : 3
- Hazard labels (DOT) :



- Packing group (DOT) : II

Additional information

- Other information : No supplementary information available.
- Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %
Naphthalene (91-20-3)	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	0.1 %
Cumene (98-82-8)	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %
Ethylbenzene (100-41-4)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	0.1 %
Toluene (108-88-3)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %
Benzene (71-43-2)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	0.1 %
Furan (110-00-9)	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	0.1 %

SERVICE PRO INTAKE VALVE CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Propylene oxide (75-56-9)	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	10000
SARA Section 313 - Emission Reporting	0.1 %

Acetaldehyde (75-07-0)	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	0.1 %


15.2. US State regulations

SP2313

State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	---

SECTION 16: Other information

Indication of changes	: None.
Date of issue	: 12/31/2014
Other information	: None.
NFPA health hazard	: 2
NFPA fire hazard	: 3
NFPA reactivity	: 0



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.