

SERVICE PRO HIGH TEMPERATURE DOT 3 BRAKE FLUID

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 05/28/2014

Revision date: 05/28/2014

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SERVICE PRO HIGH TEMPERATURE DOT 3 BRAKE FLUID
Product code : SP6001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : DOT 3 brake fluid.

1.3. Details of the supplier of the safety data sheet

The Penray Companies, Inc.
440 Denniston Ct.
Wheeling, IL 60090
T (800) 373-6729

Manufactured for:
AIOD
P.O. Box 1861
Montrose, CO 81402-1861
970-249-6336

1.4. Emergency telephone number

Emergency number : (800) 373-6729
CHEMTREC (800) 424-9300
CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Serious Eye Damage/Eye Irritation 1
Acute Oral Toxicity 4

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

DANGER

Hazard statements (GHS-US) :

Causes serious eye damage. Harmful if swallowed

Precautionary statements (GHS-US) :

Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection/face protection.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

27 % of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|------------------------------------|--------------------|-------|-----------------------|
| Diethylene glycol | (CAS No) 111-46-6 | 15-25 | Acute Tox. 4 (Oral) |
| Triethylene glycol monobutyl ether | (CAS No) 143-22-6 | 15-30 | Eye Dam. 1 |
| Diethylene glycol monobutyl ether | (CAS No) 112-34-5 | 10-20 | |
| Ethanol, 2-(2-propoxyethoxy)- | (CAS No) 6881-94-3 | 5-10 | |

SERVICE PRO HIGH TEMPERATURE DOT 3 BRAKE FLUID

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Name | Product identifier | % | GHS-US classification |
|---|--------------------|---|-----------------------|
| The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. | | | |

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Do not swallow. Avoid breathing gas/fumes/vapor/spray. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place

7.3. Specific end use(s)

Not available.

SERVICE PRO HIGH TEMPERATURE DOT 3 BRAKE FLUID

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Diethylene glycol (111-46-6) | | |
|------------------------------|-----------|-----------------|
| USA ACGIH | ACGIH TWA | Not applicable. |
| USA OSHA | OSHA PEL | Not applicable. |

| Triethylene glycol monobutyl ether (143-22-6) | | |
|---|-----------|-----------------|
| USA ACGIH | ACGIH TWA | Not applicable. |
| USA OSHA | OSHA PEL | Not applicable. |

| 3,6,9,12-Tetraoxahexadecan-1-ol (1559-34-8) | | |
|---|-----------|-----------------|
| USA ACGIH | ACGIH TWA | Not applicable. |
| USA OSHA | OSHA PEL | Not applicable. |

8.2. Exposure controls

| | | |
|----------------------------------|---|--|
| Appropriate engineering controls | : | Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. |
| Personal protective equipment | : | Avoid all unnecessary exposure. |
| Hand protection | : | Wear suitable gloves. |
| Eye protection | : | Safety glasses or goggles are recommended when using product. |
| Skin and body protection | : | Wear suitable protective clothing. |
| Respiratory protection | : | In case of insufficient ventilation, wear suitable respiratory equipment. |
| Environmental exposure controls | : | Maintain levels below Community environmental protection thresholds. |
| Other information | : | Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | | |
|--|---|---------------------------------|
| Physical state | : | Liquid. |
| Appearance | : | No data available. |
| Colour | : | Amber. |
| Odour | : | Mild. |
| Odour threshold | : | No data available. |
| pH | : | 8.6 |
| Relative evaporation rate (butylacetate=1) | : | No data available. |
| Melting point | : | No data available. |
| Freezing point | : | < -50 °C (< -58 °F) |
| Boiling point | : | > 232 °C (> 560 °F) @ 760 mm Hg |
| Flash point | : | > 121 °C (> 250 °F) |
| Self ignition temperature | : | 310 °C (590 °F) |
| Decomposition temperature | : | No data available. |
| Flammability (solid, gas) | : | Not flammable. |
| Vapour pressure | : | No data available. |
| Relative vapour density at 20 °C | : | No data available. |
| Relative density | : | 1.06 |
| Solubility | : | Soluble in water. |
| Log Pow | : | No data available. |
| Log Kow | : | No data available. |
| Viscosity, kinematic | : | No data available. |
| Viscosity, dynamic | : | No data available. |
| Explosive properties | : | No data available. |
| Oxidising properties | : | No data available. |
| Explosive limits | : | No data available. |

9.2. Other information

No additional information available

SERVICE PRO HIGH TEMPERATURE DOT 3 BRAKE FLUID

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| SP6001 | |
|----------------------------|--------------------|
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | No data available. |

| Diethylene glycol (111-46-6) | |
|------------------------------|-------------|
| LD50 oral rat | 12565 mg/kg |
| LD50 dermal rabbit | 11890 mg/kg |

| Triethylene glycol monobutyl ether (143-22-6) | |
|---|------------|
| LD50 oral rat | 5300 mg/kg |
| LD50 dermal rabbit | 3480 mg/kg |

| 3,6,9,12-Tetraoxahexadecan-1-ol (1559-34-8) | |
|---|--------------|
| LD50 oral rat | 5175 mg/kg |
| LD50 dermal rat | > 4000 mg/kg |

Skin corrosion/irritation : Based on available data, the classification criteria are not met.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Reproductive toxicity : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure) : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure) : Based on available data, the classification criteria are not met.

Aspiration hazard : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

| SP6001 | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| SP6001 | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

SERVICE PRO HIGH TEMPERATURE DOT 3 BRAKE FLUID

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

Diethylene glycol (111-46-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

Triethylene glycol monobutyl ether (143-22-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

3,6,9,12-Tetraoxahexadecan-1-ol (1559-34-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

SP6001

State or local regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

| IARC | International Agency for Research on Cancer. |
|------|--|
| | 1 - Carcinogenic to humans; 2A - Probably carcinogenic to humans; 2B - Possibly carcinogenic to humans; 3 - Not classifiable; 4 - Probably not carcinogenic to humans. |
| NTP | National Toxicology Program. |
| | 1 - Evidence of Carcinogenicity; 2 - Known Human Carcinogens; 3 - Reasonably anticipated to be Human Carcinogen; 4 - Substances delisted from report on Carcinogens; 5 - Twelfth Report - Items under consideration. |


SERVICE PRO HIGH TEMPERATURE DOT 3 BRAKE FLUID

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 16: Other information

Indication of changes : None.
Date of issue : 05/28/2014
Other information : None.



NFPA health hazard : 2
NFPA fire hazard : 1
NFPA reactivity : 0

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product