

## SERVICE PRO® ALL MAKES • ALL MODELS UNIVERSAL FORMULA ANTIFREEZE/COOLANT

Manufactured with virgin base products

**DESCRIPTION:** SERVICE PRO® All Makes • All Models Universal Formula Antifreeze/Coolant is recommended, compatible, and formulated for use with ANY antifreeze/coolant in ANY make or model of car or light duty truck with aluminum and other engine metals. This OAT technology formulation has a concentrated blend of premium long lasting inhibitors to offer extended life protection for up to 5 years or 150,000 miles\* against temperature extremes and the ravages of rust, corrosion, and premature water pump failure. When used as directed, SERVICE PRO® All Makes • All Models Universal Formula Antifreeze/Coolant may be added to the antifreeze/coolant of ANY make or model of car or light duty truck on the road, foreign or domestic.

\*Provides extended life protection when added to any extended life antifreeze/coolant or with complete flush and fill.

**PRODUCT SPECIFICATIONS:** When used as directed, SERVICE PRO® All Makes • All Models Universal Formula Antifreeze/Coolant:

- Meets ASTM D3306, D4985
- May be added to the antifreeze/ coolant of ANY make or model of automobile and light duty truck on the road, foreign or domestic
- Prevents freeze-ups, overheating, and boilovers
- May be added to ANY color antifreeze/coolant
- Protects aluminum and other engine metals
- Provides a silicate and phosphate free formulation for long lasting inhibition and corrosion protection

		<b>Typical Values</b>
Inhibited Glycols		98%
Total Water		2%
Dye		Trace
<b>Properties</b>		
Color		Yellow
Odor		Characteristic
Ash Content	ASTM D1119	1.20 % by weight
pH 50% by Volume	ASTM D1287	8.7
Reserve Alkalinity	ASTM D1121	5.15
Specific Gravity at 20/20° C	ASTM D1122	1.0687
50% by Volume Solution		
Freezing Point	ASTM D1177	-34.0°F (-37.0°C)
50% by Volume Solution		
Boiling Point *	ASTM D1120	226° F (108°C)
50% by Volume Solution		
Foam Test	ASTM D1881	50 mL/1.0 sec. max break



\* Under standard pressure

