

SERVICE PRO® PREMIUM FULL SYNTHETIC GL-5 GEAR OILS

Manufactured with virgin base oils

DESCRIPTION: SERVICE PRO® Premium Full Synthetic GL-5 Gear Oils are multi-purpose gear lubricants designed for API Service Classification “GL-5” and “MT-1”. SERVICE PRO® Premium Full Synthetic GL-5 Gear Oils are compounded with highly refined synthetic base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust preventions, low pour point, and anti-foaming performance. They are fully formulated for all limited slip differentials.

APPLICATION: SERVICE PRO® Premium Full Synthetic GL-5 Gear Oils meet the requirements of U.S. Military Specification MIL-L-2105D, MIL-L-2105E, SAE J2360, and Mack GO-J. They are recommended for use in limited slip and conventional differentials of heavy duty trucks, cars, light trucks and sport utility vehicles. Always check owner’s manual for proper recommendation. Note: These products are not approved for Eaton Roadranger and ArvinMeritor Extended Warranties. For those applications use Purus Full Synthetic Gear Lubricant.

**PERFORMANCE
BENEFITS:**

- Reduced wear
- Long service life
- Exceptional low temperature performance
- Reduces drag for optimum fuel economy
- Full Limited Slip performance

TYPICAL PROPERTIES:	Viscosity Grade	75W-90	75W-140
	Pour Point Deg F.	-40	-40
	Flash Point, COC, °F	410	420
	Viscosity		
	@ 40°C, cSt	86.6	178
	@ 100°C, cSt	14.8	27.6
	Viscosity Index	180	194
	Gravity, API	30.65	32.9
	Rust Test, ASTM D665	Pass	Pass