

SERVICE PRO[®] ANTIFREEZE/COOLANT- ORANGE

FOR USE IN GM[®] CARS AND TRUCKS REQUIRING DEX-COOL[®]

Manufactured with virgin base products

DESCRIPTION: SERVICE PRO[®] Orange Antifreeze/ Coolant for use in GM[®] Cars and Trucks requiring DEX-COOL[®] is a premium carboxylate-based Organic Acid Technology (OAT) virgin ethylene glycol-based fluid. Specially formulated with industry-leading additives, this product provides optimum performance in vehicles requiring DEX-COOL[®]* under GM 6277M.

- PERFORMANCE BENEFITS:**
- Premium quality, extended life coolant.
 - Provides up to 5 years or 150,000 miles of protection.
 - Free of phosphate, borates, nitrites, silicates, and amines.
 - Protects against corrosion of all cooling system metals, including aluminum.
 - High-quality defoamer system, non-harmful to hoses, plastics or gaskets.
 - Compatible with major brands of extended life Organic Acid Technology and Hybrid Organic Acid Technology (OAT & HOAT)-type coolant/antifreeze. Specifically formulated to meet original equipment manufacturer equivalent extended life coolants including but not limited to the DEX-COOL[®]* under GM 6277M.

TYPICAL PROPERTIES:

	ASTM Method	Concentrate	50/50
Glycols base Antifreeze Conc., mass %	GC	>95	>49
Bittering Agent		Yes	Yes
Water Content, mass %	D1123	<4	50.8
Specific Gravity @ 60°F	D1122	1.117	1.069
pH	D1287	8.7	8.4
Reserve Alkalinity, ml	D1121	5.2	2.56
Storage Stability, min.		5 years	5 years
Effect on Non-Metals	D1882	No Effect	No Effect
Cavitation Erosion Rating	D2809	8 min	8 min
Foam Test, ml/sec	D1881	<50/3	<50/3
Fluid Color	Visual	Flor Orange	Flor Orange
Coolant/Antifreeze % 50/50 Freezing Point	D1177	-34°F (-36°C)	-34°F (-36°C)
Coolant/Antifreeze % 50/50 Boiling Point	D1120	226°F (108°C)	226°F (108°C)
Ash Content	D1119	<5.0	<2.5
Chloride (mg/L)	D3634	<25	<25
Silicon (as SiO ₃)	D6130	<10	<10



Updated: 07/2015



SERVICE PRO

SERVICE PRO[®] ANTIFREEZE/COOLANT- **ORANGE** FOR USE IN GM[®] CARS AND TRUCKS REQUIRING DEX-COOL[®] Manufactured with virgin base products

SERVICE PRO[®] Orange Antifreeze/ Coolant for use in GM[®] Cars and Trucks requiring DEX-COOL[®] meets the requirements of: **

ASTM D3306
ASTM D4985
Chrysler MS-7170
Chrysler MS-9769
Chrysler MS-12106
Ford WSS-M97B44-D
GM B 040 1065 - GM 6277M
GM 6277M (DEX-COOL[®])
Navistar CEMS B-1 Type I
SAE J1034

Always consult your vehicle owner's manual for proper fluid removal and flushing procedures. Typical properties, are not to be construed as specifications.

*Not manufactured for or licensed by General Motors Corporation. GM[®] and DEX-COOL[®] are registered trademarks of the General Motors Corporation.

**Meets performance requirements but may or may not meet certain chemical requirements.



AIOD

Updated: 07/2015