

**SAFETY DATA SHEET**

**SECTION I IDENTIFICATION**

PRODUCT NAME: **SERVICE PRO WET SHINE TIRE DRESSING** Pg. 1/4  
PRODUCT CODE: Fluid 2-5584 P/N: SP5584AI - SP5585AI - SP5590AI Version 4  
CHEMICAL FAMILY: PETROLEUM DISTILLATE SOLUTION 4/22/2015  
Meets GHS requirements

SUPPLIER: CUL-MAC INDUSTRIES, INC.  
ADDRESS: 3720 S. VENOY  
WAYNE, MI 48184  
PHONE: (734) 728-9700

MANUFACTURED FOR: AIOD  
ADDRESS: PO BOX 1861  
MONTROSE, CO 81402  
PHONE: (800) 313-2463  
EMERGENCY PHONE: (866) 214-4235 (3E COMPANY)

**SECTION II HAZARD IDENTIFICATION**

ROUTES OF ENTRY:



Skin, Eyes, Ingestion, Inhalation

HEALTH HAZARD STATEMENTS:

H303:  
H313:  
H319:  
H333:

**WARNING:**  
May be Harmful if Swallowed  
May be Harmful in Contact with Skin  
Causes Serious Eye Irritation  
May be Harmful if Inhaled

PREVENTION PRECAUTIONARY STATEMENTS:

P264:

Wash Hands Thoroughly After Handling

RESPONSE PRECAUTIONARY STATEMENTS:

P312:  
P305+P351+P338:  
P337+P313:  
P304+P312:

Call a POISON CENTER or Doctor if you Feel Unwell  
IF IN EYES: Rinse Cautiously with Water for Several Minutes. Remove Contact Lenses, if Present and Easy to do so. Continue Rinsing.  
If Eye Irritation Persists: Get Medical Advice  
IF INHALED: Call a POISON CENTER or Doctor if you Feel Unwell

CARCINOGENICITY:

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA, or ACGIH.

**SECTION III COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL: % by wt. CAS # OSHA PEL ACGIH TLV

All Ingredients Are Non-Hazardous According To OSHA CFR 29. Part 1910.1200, Subpart Z

PRODUCT NAME: **SERVICE PRO WET SHINE TIRE DRESSING**  
PRODUCT CODE: Fluid 2-5584 P/N: SP5584AI - SP5585AI - SP5590AI  
CHEMICAL FAMILY: PETROLEUM DISTILLATE SOLUTION

Pg. 2/4  
Version 4  
4/22/2015

Meets GHS requirements

#### SECTION IV FIRST AID MEASURES

**SKIN CONTACT:** Remove contaminated clothing; wash under shower with soap and water for 15 minutes.  
Seek medical attention if irritation occurs.

**EYE CONTACT:** Flush immediately with gently running water for a minimum of 15 minutes.

**INGESTION:** Do not induce vomiting, feed egg whites or milk or drink large quantities of water.  
Call physician.

**INHALATION:** Move to fresh air

#### SECTION V FIRE FIGHTING MEASURES

**FLASH POINT:** N/A

**EXTINGUISHING MEDIA:** As for surrounding fire

**SPECIAL PROCEDURES:** N/A

**UNUSUAL HAZARDS:** N/A

#### SECTION VI ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURES:** Material can be slippery. Dike area and place absorbed material in proper containers for disposal. Prevent spills from entering storm sewers or drains.

#### SECTION VII HANDLING & STORAGE

**WASTE DISPOSAL METHOD:** Reuse or reprocess if possible. Dispose in accordance with all applicable regulations

**SPECIAL PRECAUTIONS:** Handle in accordance with good industrial hygiene and safety precautions.

**STORAGE:** Store at room temperature. Seal container after use.

#### SECTION VIII EXPOSURE CONTROLS - PERSONAL PROTECTION



**VENTILATION:** Use good general ventilation

**RESPIRATORY PROTECTION:** Not generally needed

**GLOVES:** Rubber gloves are recommended for sensitive skin.

**EYE PROTECTION:** Chemical splash goggles when transferring is taking place

**CLOTHING AND FOOTWEAR:** Not generally needed

PRODUCT NAME: **SERVICE PRO WET SHINE TIRE DRESSING**  
PRODUCT CODE: Fluid 2-5584 P/N: SP5584AI - SP5585AI - SP5590AI  
CHEMICAL FAMILY: PETROLEUM DISTILLATE SOLUTION

Pg. 3/4  
Version 4  
4/22/2015

Meets GHS requirements

**SECTION IX PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>BOILING POINT:</b>	> 464° F	<b>pH:</b>	5.0 - 5.5
<b>FREEZING POINT:</b>	< 32° F	<b>SPECIFIC GRAVITY:</b>	0.819
<b>VAPOR PRESSURE:</b>	N/A	<b>PERCENT VOLATILE:</b>	65
<b>VAPOR DENSITY (AIR = 1):</b>	N/A	<b>APPEARANCE:</b>	Clear Viscous Liquid
<b>SOLUBILITY IN WATER:</b>	Not Soluble	<b>ODOR:</b>	Petroleum
<b>EVAPORATION RATE:</b>	N/A		
<b>(BUTYL ACETATE = 1)</b>			

**SECTION X STABILITY AND REACTIVITY DATA**

**STABILITY:** Keep away from heat and sources of ignition

**HAZARDOUS POLYMERIZATION:** Will not occur

**INCOMPATIBILITY:** Oxidizing Agents  
**(CONDITIONS TO AVOID)**

**HAZARDOUS DECOMPOSITION:** Hazardous gases and vapors in fire are oxides of carbon

**SECTION XI TOXICOLOGICAL INFORMATION**

*This Product Has Not Been Tested As A Whole*

**SECTION XII ECOLOGICAL INFORMATION**

*This Product Has Not Been Tested As A Whole*

**SECTION XIII DISPOSAL CONSIDERATIONS**

**WASTE DESCRIPTION:** Clean up and dispose of waste in accordance with all federal, state, and local environmental regulations.

**GENERAL DISPOSAL CONSIDERATIONS:** N/A

**SECTION XIV TRANSPORT INFORMATION**

**PROPER SHIPPING NAME:** COMPOUNDS, CLEANING LIQUID

**UN/NA NUMBER:**

**HAZARD CLASS:**

**PACKING GROUP:**

**REPORTABLE QUANTITY:**

**EMERGENCY RESPONSE GUIDEBOOK:**

**PLACARD/LABELS REQUIRED:**

PRODUCT NAME: **SERVICE PRO WET SHINE TIRE DRESSING**  
PRODUCT CODE: Fluid 2-5584 P/N: SP5584AI - SP5585AI - SP5590AI  
CHEMICAL FAMILY: PETROLEUM DISTILLATE SOLUTION

Pg. 4/4  
Version 4  
4/22/2015

Meets GHS requirements

**SECTION XV REGULATORY INFORMATION**

**OSHA HAZARDOUS CHEMICAL:** No  
**SARA 302 COMPONENTS:** None  
**SARA 311/312:** Immediate (X) Delayed ( ) Fire ( ) Reactive ( )  
Sudden release of Pressure ( )  
**SARA 313 COMPONENTS:** None

**SECTION XVI OTHER INFORMATION**

**HMIS:** Health = 1; Flammability = 0; Reactivity = 0; Personal Protection Equipment = B

**DISCLAIMER**

The information herein has been from sources believed to be accurate, reliable and up to date to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources and do not make any warranties nor assume any liability from its use or misuse.

**End of SDS**