

SAFETY DATA SHEET

SECTION I IDENTIFICATION

PRODUCT NAME: **SERVICE PRO SILICONE DETAILER** Pg. 1/4
PRODUCT CODE: Fluid BR-0547 P/N SP6110AI-SP6113AI Version 3
PRODUCT USE: AUTOMOTIVE RECONDITIONING PRODUCT 8/8/2013
Meets GHS requirements

SUPPLIER:	CUL-MAC INDUSTRIES, INC.	MANUFACTURED FOR:	AIOD
ADDRESS:	3720 S. VENOY	ADDRESS:	PO BOX 1861
	WAYNE, MI 48184		MONTROSE, CO 81402
PHONE:	(734) 728-9700	PHONE:	(800) 313-2463
		EMERGENCY PHONE:	(866) 214-4235 (3E COMPANY)

SECTION II HAZARD IDENTIFICATION



ROUTES OF ENTRY: Skin, Eyes, Ingestion

WARNING:

HEALTH HAZARDS: **SKIN** - Prolonged or repeated contact may cause irritation/dermatitis
(acute & chronic) **EYES** - May cause irritation to the eyes
INGESTION - May cause nausea, vomiting, and diarrhea.

CARCINOGENICITY: None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA, or ACGIH.

SECTION III COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL:	% by wt.	CAS #	OSHA PEL	ACGIH TLV
Isopropanol	1-10	63-67-0	500 ppm	500 ppm

SECTION IV FIRST AID MEASURES

SKIN CONTACT: Immediately take off all contaminated clothing. For skin contact, wash immediately with soap and water.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 min. Get medical attention or advice.

INGESTION: If the material is swallowed, get immediate medical attention. Give several glasses of water or milk.

SECTION V FIRE FIGHTING MEASURES

FLASH POINT: N/A

EXTINGUISHING MEDIA: As for surrounding fire

SPECIAL PROCEDURES: Non-combustible, substance itself does not burn

PRODUCT NAME: **SERVICE PRO SILICONE DETAILER**
PRODUCT CODE: Fluid BR-0547 P/N SP6110AI-SP6113AI
PRODUCT USE: AUTOMOTIVE RECONDITIONING PRODUCT

Pg. 2/4
Version 3
8/8/2013

Meets GHS requirements

SECTION VI ACCIDENTAL RELEASE MEASURES


CONTAINMENT PROCEDURES: Stop the flow of material, if this is without risk. Dike the spilled material where possible.
Absorb with inert absorbent such as clay, sand or diatomaceous earth, commercial absorbents, or recover using pumps.

SECTION VII HANDLING & STORAGE

HANDLING PROCEDURES: Avoid prolonged or repeated skin contact with this material.

STORAGE PROCEDURES: Keep container tightly closed. Do not store, incinerate, or heat this material above 120° F. Do not freeze.

SECTION VIII EXPOSURE CONTROLS - PERSONAL PROTECTION



VENTILATION: Explosion proof exhaust ventilation should be used.

RESPIRATORY PROTECTION: Not generally needed

GLOVES: Rubber gloves are recommended for sensitive skin.

EYE PROTECTION: Chemical splash goggles when transferring is taking place.

CLOTHING & FOOTWEAR: Not generally needed

SECTION IX PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT:	> 212° F	pH:	7.0
FREEZING POINT:	32° F	SPECIFIC GRAVITY:	1
VAPOR PRESSURE:	< 20 mm/Hg	PERCENT VOLATILE:	N/A
VAPOR DENSITY (AIR = 1):	> 1	APPEARANCE:	Baby Blue Liquid
SOLUBILITY IN WATER:	N/A	ODOR:	Baby Powder
EVAPORATION RATE:	N/A		
(BUTYL ACETATE = 1)			

PRODUCT NAME: **SERVICE PRO SILICONE DETAILER**
PRODUCT CODE: Fluid BR-0547 P/N SP6110AI-SP6113AI
PRODUCT USE: AUTOMOTIVE RECONDITIONING PRODUCT

Pg. 3/4
Version 3
8/8/2013
Meets GHS requirements

SECTION X STABILITY AND REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

**INCOMPATIBILITY:
(CONDITIONS TO AVOID)** Strong oxidizing agents (peroxides, chlorine, strong acids)

HAZARDOUS DECOMPOSITION: None known.

SECTION XI TOXICOLOGICAL INFORMATION

Isopropyl Alcohol: Acute oral toxicity (LD50): 3600 mg/kg, 4 hours [Mouse].
Acute dermal toxicity (LD50): 12800 mg/kg, 4 hours [Rabbit].
Acute toxicity of the vapor (LC50): 16000, 8 hours [Rat].

SECTION XII ECOLOGICAL INFORMATION



Isopropyl Alcohol: Ecotoxicity in water (LC50): 100000 mg/L, 96 hours [Fathead Minnow]

SECTION XIII DISPOSAL CONSIDERATIONS

WASTE DESCRIPTION: Clean up and dispose of waste in accordance with all federal, state, and local environmental regulations.

GENERAL DISPOSAL CONSIDERATIONS: None known

SECTION XIV TRANSPORT INFORMATION

PROPER SHIPPING NAME: COMPOUNDS, CLEANING LIQUID

UN/NA NUMBER:

HAZARD CLASS:

PACKING GROUP:

REPORTABLE QUANTITY:

EMERGENCY RESPONSE GUIDEBOOK:

PLACARD/LABELS REQUIRED:

SECTION XV REGULATORY INFORMATION

OSHA HAZARDOUS CHEMICAL: No

SARA 302 COMPONENTS: None

SARA 311/312: Immediate () Delayed () Fire () Reactive ()

Sudden release of Pressure ()

SARA 313 COMPONENTS: None

PRODUCT NAME: **SERVICE PRO SILICONE DETAILER**
PRODUCT CODE: Fluid BR-0547 P/N SP6110AI-SP6113AI
PRODUCT USE AUTOMOTIVE RECONDITIONING PRODUCT

Pg. 4/4
Version 3
8/8/2013
Meets GHS requirements

SECTION XVI OTHER INFORMATION

HMIS: Health = 2; Flammability = 0; Reactivity = 0

DISCLAIMER

The information herein has been from sources believed to be accurate, reliable and up to date to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources and do not make any warranties nor assume any liability from its use or misuse.

End of SDS