

**SAFETY DATA SHEET**

**SECTION I COMPANY INFORMATION**

PRODUCT NAME: **SERVICE PRO WATER BASE UNDERCOATING** Pg. 1/3  
PRODUCT CODE: PAC P/N SP6190AI Version 3  
CHEMICAL FAMILY: Petroleum asphalt 8/8/2013  
Meets GHS requirements

SUPPLIER:	CUL-MAC INDUSTRIES, INC.	MANUFACTURED FOR:	AIOD
ADDRESS:	3720 S. VENOY	ADDRESS:	PO BOX 1861
	WAYNE, MI 48184		MONTROSE, CO 81402
PHONE:	(734) 728-9700	PHONE:	(800) 313-2463
		EMERGENCY PHONE:	(866) 214-4235 (3E COMPANY)

**SECTION II HAZARD IDENTIFICATION**



**ROUTES OF ENTRY:** Eyes, Skin, Ingestion, Inhalation

**HEALTH HAZARDS:** **SKIN and EYES** - Hot product causes burns.  
(acute & chronic) **INGESTION** - Product has acute toxicity.  
**INHALATION** - Vapors and fumes can cause respiratory and nasal irritation

**CARCINOGENICITY:** Not listed by OSHA, IARC, OR NTP

**SECTION III COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL:	% by wt.	CAS #	OSHA PEL	ACGIH TLV
Petroleum Asphalt	35 - 65	8052-42-4	* N/E	5 mg/m3 8 hr TWA
Middle Distillate	<2	64741-44-2	5 mg/m3, 8 hr	5 mg/m3 8 hr

*\*OSHA has not established a specific PEL for asphalt fumes. They are considered as "particulate not otherwise regulated" with a PEL of 5 mg/m3 for the respirable dust and fraction and 15mg/m3 for total dust fraction.*

**SECTION IV FIRST AID MEASURES**

**SKIN CONTACT:** Wash with soap and large amounts of water. Remove contaminated clothing and wash before re-use. Get medical attention if irritation develops.

**EYE CONTACT:** Flush immediately with gently running water for a minimum of 15 minutes.

**INGESTION:** Ingestion not likely. If large amounts are swallowed, immediately call a physician.

**INHALATION:** Move to fresh air

PRODUCT NAME: **SERVICE PRO WATER BASE UNDERCOATING**  
PRODUCT CODE: PAC P/N SP6190AI  
CHEMICAL FAMILY: Petroleum asphalt

Pg. 2/3  
Version 3  
8/8/2013  
Meets GHS requirements

### SECTION V FIRE FIGHTING MEASURES

**FLASH POINT:** N/A

**EXTINGUISHING MEDIA:** Foam, carbon dioxide, dry chemical, water spray

**SPECIAL PROCEDURES:** Do not spray water directly on substance. Water may be used to cool closed containers. In a substance fire, use self-contained breathing apparatus.

**UNUSUAL HAZARDS:** None

### SECTION VI ACCIDENTAL RELEASE MEASURES

**SPILL OR LEAK PROCEDURES:** **Land Spill** - Avoid runoff into storm sewers or ditches by containment with sand or absorbent material.

### SECTION VII HANDLING & STORAGE

**WASTE DISPOSAL METHOD:** Reuse or reprocess if possible. Dispose in accordance with all applicable regulations.

**SPECIAL PRECAUTIONS:** Handle in accordance with good industrial hygiene and safety precautions.

**STORAGE:** Store at room temperature. Seal container after use.

### SECTION VIII EXPOSURE CONTROLS - PERSONAL PROTECTION



**VENTILATION:**

Use good general ventilation

**RESPIRATORY PROTECTION:** NIOSH approved supplied air respirator when exposure limits are exceeded.

**GLOVES:** Rubber gloves are recommended for sensitive skin.

**EYE PROTECTION:** Chemical splash goggles when transferring is taking place.

**CLOTHING AND FOOTWEAR:** For large spills wear chemical resistant pants and jackets.  
Wear chemical resistant footwear.

### SECTION IX PHYSICAL/CHEMICAL CHARACTERISTICS

<b>BOILING POINT:</b>	N/A	<b>pH:</b>	8.5 - 9.5
<b>FREEZING POINT:</b>	N/A	<b>SPECIFIC GRAVITY:</b>	1.0 - 1.2
<b>VAPOR PRESSURE (mm Hg):</b>	23.5	<b>PERCENT VOLATILE:</b>	30 - 50 water
<b>VAPOR DENSITY (AIR = 1):</b>	N/A	<b>APPEARANCE:</b>	brown/black liquid
<b>SOLUBILITY IN WATER:</b>	Soluble	<b>ODOR:</b>	None
<b>EVAPORATION RATE:</b>	N/A		
<b>(ETHYL ETHER = 1)</b>			

PRODUCT NAME: SERVICE PRO WATER BASE UNDERCOATING  
PRODUCT CODE: PAC P/N SP6190AI  
CHEMICAL FAMILY: Petroleum asphalt

Pg. 3/3  
Version 3  
8/8/2013

Meets GHS requirements

**SECTION X STABILITY AND REACTIVITY DATA**

**STABILITY:** Stable under normal use

**HAZARDOUS POLYMERIZATION:** Not expected to occur

**INCOMPATIBILITY:** Avoid contact with strong oxidizers

**HAZARDOUS DECOMPOSITION:** Carbon dioxide, carbon monoxide, sulfur oxides, hydrogen sulfide and various hydrocarbon fractions.

**SECTION XI TOXICOLOGICAL INFORMATION**

This product has not been tested as a whole

**SECTION XII ECOLOGICAL INFORMATION**

**Petroleum asphalt** Not known to cause any acute or chronic toxicity to aquatic organisms due to its extremely low water solubility.

**SECTION XIII DISPOSAL CONSIDERATIONS**

**WASTE DESCRIPTION:** Clean up and dispose of waste in accordance with all federal, state, and local environmental regulations.

**GENERAL DISPOSAL CONSIDERATIONS:** None known

**SECTION XIV TRANSPORT INFORMATION**

**PROPER SHIPPING NAME:** Not DOT regulated

**UN/NA NUMBER:**

**HAZARD CLASS:**

**PACKING GROUP:**

**EMERGENCY RESPONSE GUIDEBOOK:**

**PLACARD/LABELS REQUIRED:**

**SECTION XV REGULATORY INFORMATION**

**OSHA HAZARDOUS CHEMICAL:** none

**SARA 302 COMPONENTS:** none

**SARA 311/312:** Immediate ( ) Delayed ( ) Fire (X) Reactive ( )  
Sudden release of Pressure ( )

**SARA 313 COMPONENTS:** none

**SECTION XVI OTHER INFORMATION**

**HMIS:** Health = 2; Flammability = 0; Reactivity = 0

**DISCLAIMER**

The information herein has been from sources believed to be accurate, reliable and up to date to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources and do not make any warranties nor assume any liability from its use or misuse.

**End of SDS**