

SERVICE PRO® PREMIUM POWER STEERING FLUID

DESCRIPTION: SERVICE PRO® Premium Power Steering Fluid is formulated using premium Group II base oils with advanced chemistry offering excellent protection and performance in all power steering systems. It will provide exceptional anti-wear, anti-corrosion, and anti-oxidation control eliminating pump squeal.

- PERFORMANCE BENEFITS:**
- Recommended “top tier” power steering fluid for use in GM, Chrysler and Ford cars and trucks
 - Suitable for use in European cars specifying “mineral oil” based fluids
 - Protects and conditions power steering system
 - Keeps seals pliable and efficient (will not harm seals)
 - Extends power steering system life
 - Protects against wear and corrosion
 - Eliminates pump cavitations and slippage

Not recommended for complete fluid replacement in applications requiring the use of fully synthetic hydraulic fluid in the power steering system. NOT INTENDED FOR USE IN AUTOMATIC TRANSMISSIONS.

APPLICATIONS: *Meets industry specifications and is recommended for service fill replacement in power steering systems requiring vehicle specifications listed below:*

Audi PN G002000 (mineral oil base)
DaimlerChrysler MS1872 & MS5931F
Ford MERCON, Ford M2C138-CJ, M2C33-F, and ESW-M2C128 C&D
GM 9985010 Saginaw Power Steering Systems
GM DEXRON®, DEXRON® II, II-E, III, III-G*

Kia - USA sales
Mercedes Benz PN 00 989 8803 (mineral oil base)
Navistar TMS 6810
Saab PM 30 09 800
Subaru PN K0Z09A0080
Volkswagen TL-VW-570-26 (mineral oil base)

TYPICAL PROPERTIES:	Viscosity @ 40°C	32-40
	Viscosity @ 100°C	6.8-7.6
	SUS @ 104° F	150-190
	SUS @ 210° F	35-45
	Viscosity Index	Min. 140
	Pour Point ° F	Max. -40
	Flash Point ° F	Min 400 ° F



Updated: 05/13

SPSPSPB