

## SERVICE PRO® 50/50 PREDILUTED PREMIUM ANTIFREEZE & COOLANT

Manufactured with virgin base products

**DESCRIPTION:** SERVICE PRO® 50/50 Prediluted Premium Antifreeze & Coolant is premixed with deionized and demineralized water that meets or exceeds the performance requirements of Type IV water of: ASTM D 1193.

SERVICE PRO® 50/50 Prediluted Premium Antifreeze & Coolant protects all common cooling system metals including solder, copper, brass, steel, cast iron and aluminum. This low-silicate formula provides excellent heat rejecting aluminum protection for all passenger car and light duty truck cooling systems.

SERVICE PRO® 50/50 Prediluted Premium Antifreeze & Coolant also provides outstanding protection for heavy duty applications when combined with supplemental coolant additives (SCA).

When used as directed, SERVICE PRO® 50/50 Prediluted Premium Antifreeze & Coolant meets or exceeds the performance requirements of the following specifications:

PRODUCT SPECIFICATIONS:	• ASTM D-3306	• Ford New Holland 9-86	• Caterpillar
	• ASTM D-4985	• Detroit Diesel 7SE298	• John Deere 8650-5
	• SAE J 1941	• Case Corp MS1710	• Thermo-King
	• GM 1899M	• GM 1825M	• Navistar
	• Cummins 90T8-4	• GSA CID A-A-52624	• Freightliner 48-22880
	• TMC RP 302B	• Chrysler MS 7170	• Volvo GM
	• Mack Truck	• EMD M.I. 1748E	• Waukesha 4-1974D

Antifreeze/Coolant Concentrate  
Water  
Dye

### Typical Values\*\*

51%  
49%  
Trace

### Properties

Color	
Odor	
Ash Content	ASTM D1119
pH	ASTM D1287
Reserve Alkalinity	ASTM D1121
Specific Gravity at 20/20° C	ASTM D1122
Freezing Point	ASTM D1177
Boiling Point *	ASTM D1120
Foam Test	ASTM D1881

Green  
Characteristic  
0.23%  
10.4  
2.8 mL  
1.0687  
-34.0°F (-37.0°C)  
226° F (108°C)  
50 mL/1.0 sec. max



\* Under standard pressure



Updated 03/2016

# SERVICE PRO® 50/50 PREDILUTED PREMIUM ANTIFREEZE & COOLANT

Manufactured with virgin base products

\*\*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.