

## SERVICE PRO® ASIAN VEHICLES 50/50 PREDILUTED ANTIFREEZE/COOLANT – BLUE

Manufactured with virgin base products

**DESCRIPTION:** SERVICE PRO® Asian Blue 50/50 Prediluted Antifreeze/Coolant is a phosphate-enhanced organic acid technology (POAT) antifreeze/coolant specifically engineered for use in Asian vehicles requiring a blue coolant. It is free of silicate, borate, nitrite and amines, and will provide exceptional protection against rust and corrosion to all cooling system metals, including aluminum. SERVICE PRO® Asian 50/50 Prediluted Antifreeze/Coolant is fully compatible with other extended life coolants and provides service life protection of up to 150,000 miles or 5 years with a complete flush and fill. It meets the performance requirements of ASTM D3306 and Asian standard JIS K2234.

**PERFORMANCE  
BENEFITS:**

- Matches the OEM color and technology for Asian vehicles requiring a blue extended life coolant
- Protects aluminum and all the other engine metals
- Prevents freeze-up and boilover under extreme condition

Honda/Acura	1990 and up
Mitsubishi	Mirage and Outlander 2001 and up, Raider 2006 and up, Lancer 2012 and up
Nissan/Infiniti	2009 and up
Subaru	2009 and up
Suzuki	2010 and up

**TYPICAL  
PROPERTIES\*\*:**

Antifreeze/Coolant Concentrate		51%
Total Water		49%
Dye		Trace
Color	Visual	Blue
Odor	Olfactory	Characteristic
Ash Content	ASTM D1119	0.82
pH	ASTM D1287	7.7
Reserve Alkalinity	ASTM D1121	2.6
Specific Gravity at 20/20° C	ASTM D1122	1.066
Freezing Point	ASTM D1177	-36.2°F (-37.9°C)
Boiling Point *	ASTM D1120	229° F (109.5°C)
Foam Test	ASTM D1881	50 mL/1.0 sec. max break time

\* Under standard atmospheric pressure



SP AF ASIANBL5050  
PG 1  
Updated 05/2018

# **SERVICE PRO® ASIAN VEHICLES**

## **50/50 PREDILUTED ANTIFREEZE/COOLANT-BLUE**

**Manufactured with virgin base products**

\*\*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



# SERVICE PRO® ASIAN VEHICLES ANTIFREEZE/COOLANT – BLUE

Manufactured with virgin base products

**DESCRIPTION:** SERVICE PRO® Asian Blue Antifreeze/Coolant is a phosphate-enhanced organic acid technology (POAT) antifreeze/coolant specifically engineered for use in Asian vehicles requiring a blue coolant. It is free of silicate, borate, nitrite and amines, and will provide exceptional protection against rust and corrosion to all cooling system metals, including aluminum. SERVICE PRO® Asian Antifreeze/Coolant is fully compatible with other extended life coolants and provides service life protection of up to 150,000 miles or 5 years with a complete flush and fill. It meets the performance requirements of ASTM D3306 and Asian standard JIS K2234.

**PERFORMANCE  
BENEFITS:**

- Matches the OEM color and technology for Asian vehicles requiring a blue extended life coolant
- Protects aluminum and all the other engine metals
- Prevents freeze-up and boilover under extreme condition

<b>Honda/Acura</b>	<b>1990 and up</b>
<b>Mitsubishi</b>	<b>Mirage and Outlander 2001 and up, Raider 2006 and up, Lancer 2012 and up</b>
<b>Nissan/Infiniti</b>	<b>2009 and up</b>
<b>Subaru</b>	<b>2009 and up</b>
<b>Suzuki</b>	<b>2010 and up</b>

**TYPICAL  
PROPERTIES\*\*:**

Antifreeze/Coolant Concentrate		97.1%
Total Water		2.9%
Dye		Trace
Color	Visual	Blue
Odor	Olfactory	Characteristic
Ash Content	ASTM D1119	1.62
pH	ASTM D1287	7.7
Reserve Alkalinity	ASTM D1121	5.7
Specific Gravity at 20/20° C	ASTM D1122	1.122
Boiling Point *	ASTM D1120	343°F (173°C)
Foam Test	ASTM D1881	35 mL/1.5 sec. max break time

\* Under standard atmospheric pressure



# **SERVICE PRO® ASIAN VEHICLES**

## **ANTIFREEZE/COOLANT-BLUE**

**Manufactured with virgin base products**

\*\*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

