

SERVICE PRO® ASIAN VEHICLES 50/50 PREDILUTED ANTIFREEZE/COOLANT – RED

Manufactured with virgin base products

DESCRIPTION:

SERVICE PRO® Asian Red 50/50 Prediluted Antifreeze/ Coolant is a phosphate-enhanced organic acid technology (POAT) antifreeze/coolant specifically engineered for use in Asian vehicles requiring a red coolant. It is free of silicate, borate, nitrite and amines, and will provide exceptional protection against rust and corrosion to all cooling system metals, including aluminum. SERVICE PRO® Asian 50/50 Prediluted Antifreeze/Coolant is fully compatible with other extended life coolants and provides service life protection of up to 150,000 miles or 5 years with a complete flush and fill. It meets the performance requirements of ASTM D3306 and Asian standard JIS K2234.


PERFORMANCE BENEFITS:

- Matches the OEM color and technology for Asian vehicles requiring a red extended life coolant
- Protects aluminum and all the other engine metals
- Prevents freeze-up and boilover under extreme condition

Toyota	1990 and up
Lexus	1990 and up
Scion	2004 and up

TYPICAL PROPERTIES**:

Antifreeze/Coolant Concentrate		51%
Total Water		49%
Dye		Trace
Color	Visual	Red
Odor	Olfactory	Characteristic
Ash Content	ASTM D1119	0.82
pH	ASTM D1287	7.7
Reserve Alkalinity	ASTM D1121	2.6
Specific Gravity at 20/20° C	ASTM D1122	1.066
Freezing Point	ASTM D1177	-36.2° F (-37.9°C)
Boiling Point *	ASTM D1120	229° F (109.5°C)
Foam Test	ASTM D1881	50 mL/1.0sec. max break time



SP AF ASIANRD5050

PG 1

Updated 05/2018



SERVICE PRO® ASIAN VEHICLES

50/50 PREDILUTED ANTIFREEZE/COOLANT-RED

Manufactured with virgin base products

**Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

SERVICE PRO® ASIAN VEHICLES ANTIFREEZE/COOLANT – RED

Manufactured with virgin base products

DESCRIPTION:

SERVICE PRO® Asian Red Antifreeze/ Coolant is a phosphate-enhanced organic acid technology (POAT) antifreeze/coolant specifically engineered for use in Asian vehicles requiring a red coolant. It is free of silicate, borate, nitrite and amines, and will provide exceptional protection against rust and corrosion to all cooling system metals, including aluminum. SERVICE PRO® Asian Antifreeze/Coolant is fully compatible with other extended life coolants and provides service life protection of up to 150,000 miles or 5 years with a complete flush and fill. It meets the performance requirements of ASTM D3306 and Asian standard JIS K2234.

**PERFORMANCE
BENEFITS:**

- Matches the OEM color and technology for Asian vehicles requiring a red extended life coolant
- Protects aluminum and all the other engine metals
- Prevents freeze-up and boilover under extreme condition

Toyota	1990 and up
Lexus	1990 and up
Scion	2004 and up

**TYPICAL
PROPERTIES**:**

Antifreeze/Coolant Concentrate		97.1%
Total Water		2.9%
Dye		Trace
Color	Visual	Red
Odor	Olfactory	Characteristic
Ash Content	ASTM D1119	0.82
pH	ASTM D1287	7.7
Reserve Alkalinity	ASTM D1121	5.7
Specific Gravity at 20/20° C	ASTM D1122	1.066
Boiling Point *	ASTM D1120	317°F (158°C)
Foam Test	ASTM D1881	35 mL/1.5 sec. max break time

SP AF ASIANRD

PG 1

Updated 05/2018



SERVICE PRO® ASIAN VEHICLES

ANTIFREEZE/COOLANT-RED

Manufactured with virgin base products

**Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.