

# SERVICE PRO® PREMIUM SYNTHETIC BLEND HIGH MILEAGE API SN PLUS MOTOR OILS

**Manufactured with highly refined base oils and licensed additive technology**

**DESCRIPTION:** SERVICE PRO® Premium Synthetic Blend High Mileage API SN PLUS Motor Oils are formulated to provide older engines protection under severe operating conditions. SERVICE PRO® Premium Synthetic Blend High Mileage API SN PLUS Motor Oils blended from selected and highly refined synthetic and conventional base oils compounded to provide protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits. API SN PLUS helps prevent pre-ignition and wear, and provides improved cleanliness and fuel economy. These motor oils may be used over a wide temperature range and are formulated to meet the requirements of high mileage vehicles that have accumulated over 75,000 miles and may be experiencing an increase in oil consumption or an increase in leakage.

SERVICE PRO® Premium Synthetic Blend High Mileage API SN PLUS Motor Oils are engineered to protect against high temperature oxidation and viscosity breakdown, minimize start-up wear, and control engine deposits. They are also designed to increase fuel economy, lower engine operating temperatures and extend engine life. Please refer to your service manual for manufacturer's API Service recommendations. Meet or exceeds requirements of API Service Category's SN PLUS. SN, SM, SL, and SJ, Ford WSS-M2C945-B1 (5W-20) and Ford WSS-M2C946-B1 (5W-30),

**PERFORMANCE  
BENEFITS:**

- Helps reduce oil consumption and leaks
- Fuel efficient formulations
- Helps reduce engine wear and corrosion
- Excellent low temperature pour point
- Increased emission protection

**TYPICAL  
PROPERTIES\*:**

SAE Grade	5W-20	5W-30	10W-30	10W-40	20W-50
Viscosity					
@40 Deg. C, cSt	46.63	64.6	72	87.83	157
@100 Deg. C, cSt	8.22	10.9	11.1	13.3	18.5
Flash, COC, °F	395	425	420	420	430
Viscosity Index	151	161	144	152	132
API Gravity	32.5	33.5	31.5	32	29.9
Specific Gravity	0.8619	0.8576	0.8681	0.8654	0.8767
Pour Point, °F	-35	-35	-35	-30	-25
API Performance	SN PLUS	SN PLUS	SN PLUS	SN PLUS	SN PLUS



Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information



SPWNSYNBHM

Updated: 04/18