

SERVICE PRO WHITE LITHIUM GREASE

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 08/19/2014

Revision date: 08/19/2014

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SERVICE PRO WHITE LITHIUM GREASE
Product code : SP2685

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : White Lithium Grease.

1.3. Details of the supplier of the safety data sheet

The Penray Companies, Inc.
440 Denniston Ct.
Wheeling, IL 60090
T (800) 373-6729

Manufactured for:
AIOD
P.O. Box 1861
Montrose, CO 81402
970-240-4176

1.4. Emergency telephone number

Emergency number : (800) 373-6729
CHEMTREC (800) 424-9300
CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Aerosol 1
Gases Under Pressure - Liquefied Gas
Acute toxicity 4 (Inhalation)
Skin irritation 2
Eye irritation 2A
Carcinogenicity 2
Reproductive toxicity 2 (developmental)
Aspiration hazard 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

SERVICE PRO WHITE LITHIUM GREASE

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

2.4. Unknown acute toxicity (GHS-US)

3 percent of the mixture consists of ingredient(s) of unknown acute toxicity

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|---|---------------------|-----------|---|
| Petroleum distillates, hydrotreated light | (CAS No) 64742-47-8 | 10 - 30 | Flam. Liq. 3 Asp. Tox. 1 |
| Xylenes (o-, m-, p- isomers) | (CAS No) 1330-20-7 | 10 - 30 | Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2 Eye Irrit. 2A |
| Distillates, petroleum, hydrotreated heavy naphthenic | (CAS No) 64742-52-5 | 10 - 30 | Asp. Tox. 1 |
| Propane | (CAS No) 74-98-6 | 10 - 30 | Flam. Gas 1 Liquefied gas |
| Butane | (CAS No) 106-97-8 | 7 - 13 | Flam. Gas 1 Liquefied gas |
| Phenylethane | (CAS No) 100-41-4 | 3 - 7 | Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2 Asp. Tox. 1 |
| Zinc oxide | (CAS No) 1314-13-2 | 0.5 - 1.5 | Not classified |
| Toluene | (CAS No) 108-88-3 | 0.1 - 1 | Flam. Liq. 2 Skin Irrit. 2 Repr. 2 (developmental) STOT SE 3 STOT RE 2 Asp. Tox. 1 |

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Harmful if inhaled. Vapors may cause drowsiness and dizziness. May cause respiratory tract irritation. Intentional misuse of product by inhalation can result in asphyxiation or death.
- Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon, oxides of zinc, oxides of sulfur, hydrogen sulfide, hydrocarbons, aldehydes.

SERVICE PRO WHITE LITHIUM GREASE

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Do not swallow. Avoid breathing gas/mist/vapors/spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Petroleum distillates, hydrotreated light (64742-47-8) | | |
|--|----------------|-----------------|
| USA ACGIH | ACGIH TWA | Not applicable. |
| USA OSHA | OSHA PEL (TWA) | Not applicable. |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | | |
|--|-------------------------------------|-----------------------|
| USA ACGIH | ACGIH TWA (ppm) | 100 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 150 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |

| Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5) | | |
|--|----------------|-----------------|
| USA ACGIH | ACGIH TWA | Not applicable. |
| USA OSHA | OSHA PEL (TWA) | Not applicable. |

| Propane (74-98-6) | | |
|-------------------|-------------------------------------|------------------------|
| USA ACGIH | ACGIH TWA (ppm) | 1000 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 1800 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |

SERVICE PRO WHITE LITHIUM GREASE

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Butane (106-97-8) | | |
|-------------------|------------------|----------|
| USA ACGIH | ACGIH STEL (ppm) | 1000 ppm |

| Phenylethane (100-41-4) | | |
|-------------------------|-------------------------------------|-----------------------|
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |

| Zinc oxide (1314-13-2) | | |
|------------------------|-------------------------------------|---|
| USA ACGIH | ACGIH TWA (mg/m ³) | 2 mg/m ³ |
| USA ACGIH | ACGIH STEL (mg/m ³) | 10 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 5 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (resp) |

| Toluene (108-88-3) | | |
|--------------------|--------------------------|---------|
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 300 ppm |

8.2. Exposure controls

| | |
|----------------------------------|---|
| Appropriate engineering controls | : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. |
| Personal protective equipment | : Avoid all unnecessary exposure. |
| Hand protection | : Wear chemically resistant protective gloves. |
| Eye protection | : Wear eye protection. |
| Skin and body protection | : Wear suitable protective clothing. |
| Respiratory protection | : A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Environmental exposure controls | : Maintain levels below Community environmental protection thresholds. |
| Other information | : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---------------------------|
| Physical state | : Gas/Pressurized Liquid. |
| Appearance | : Grease. |
| Color | : Light yellow. |
| Odor | : Solvent. |
| Odor threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Flammable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : 7.14 - 7.31 lb/gal |
| Solubility | : No data available |

SERVICE PRO WHITE LITHIUM GREASE

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| | |
|----------------------|---------------------|
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, oxides of zinc, oxides of sulfur, hydrogen sulfide, hydrocarbons, aldehydes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

| SP2685 | |
|---------------------|---|
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | >1.0 but ≤5.0 mg/l/4h (Calculated using ATE values) |

| Petroleum distillates, hydrotreated light (64742-47-8) | |
|--|---------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | > 5.2 mg/l/4h |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|--|--------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | > 1700 mg/kg |
| LC50 inhalation rat | 5000 ppm/4h |

| Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5) | |
|--|---------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 5000 mg/kg |
| LC50 inhalation rat | > 5.0 mg/l/4h |

| Propane (74-98-6) | |
|---------------------|-------------|
| LC50 inhalation rat | 658 mg/l/4h |

| Butane (106-97-8) | |
|---------------------|-------------|
| LC50 inhalation rat | 658 mg/l/4h |

| Phenylethane (100-41-4) | |
|-------------------------|--------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | 15354 mg/kg |
| LC50 inhalation rat | 17.2 mg/l/4h |

SERVICE PRO WHITE LITHIUM GREASE

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Zinc oxide (1314-13-2) | |
|-------------------------------|--------------|
| LD50 oral rat | > 5000 mg/kg |

| Toluene (108-88-3) | |
|---------------------------|--------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rat | 12124 mg/kg |
| LD50 dermal rabbit | 8390 mg/kg |
| LC50 inhalation rat | 28.1 mg/l/4h |

| | |
|-----------------------------------|---|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Based on available data, the classification criteria are not met. |
| Germ cell mutagenicity | : Based on available data, the classification criteria are not met. |
| Carcinogenicity | : Suspected of causing cancer. |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|----------------------|
| IARC group | 3 - Not classifiable |

| Phenylethane (100-41-4) | |
|--|--------------------------------------|
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicity Program (NTP) Status | 1 - Evidence of Carcinogenicity |

| Toluene (108-88-3) | |
|---------------------------|----------------------|
| IARC group | 3 - Not classifiable |

| | |
|--|---|
| Reproductive toxicity | : Suspected of damaging the unborn child. |
| Specific target organ toxicity (single exposure) | : Based on available data, the classification criteria are not met. |
| Specific target organ toxicity (repeated exposure) | : Based on available data, the classification criteria are not met. |
| Aspiration hazard | : May be fatal if swallowed and enters airways. |
| Symptoms/injuries after inhalation | : Harmful if inhaled. Vapors may cause drowsiness and dizziness. May cause respiratory tract irritation. Intentional misuse of product by inhalation can result in asphyxiation or death. |
| Symptoms/injuries after skin contact | : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. |
| Symptoms/injuries after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Symptoms/injuries after ingestion | : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|-------------------|---|
| Ecology - general | : May cause long-term adverse effects in the aquatic environment. |
|-------------------|---|

12.2. Persistence and degradability

| SP2685 | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| SP2685 | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

| | |
|------------------------------|--|
| Effect on ozone layer | : No additional information available |
| Effect on the global warming | : No known ecological damage caused by this product. |

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--------------------------------|---|
| Waste disposal recommendations | : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible. |
|--------------------------------|---|

SERVICE PRO WHITE LITHIUM GREASE

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Additional information : Flammable vapors may accumulate in the container. Do not incinerate closed containers.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No. : UN1950

14.2. UN proper shipping name

Proper Shipping Name : Aerosols flammable

Department of Transportation Hazard Classes : 2.1

Hazard labels :



14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on United States SARA Section 313

| | |
|---------------------------------------|-------|
| SARA Section 313 - Emission Reporting | 1.0 % |
|---------------------------------------|-------|

Phenylethane (100-41-4)

Listed on United States SARA Section 313

| | |
|---------------------------------------|-------|
| SARA Section 313 - Emission Reporting | 0.1 % |
|---------------------------------------|-------|

Toluene (108-88-3)

Listed on United States SARA Section 313

| | |
|---------------------------------------|-------|
| SARA Section 313 - Emission Reporting | 1.0 % |
|---------------------------------------|-------|

15.3. US State regulations

SP2685

State or local regulations

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

Indication of changes : None.

Date of issue : 08/19/2014


Other information : None.

SERVICE PRO WHITE LITHIUM GREASE

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

NFPA health hazard : 2
NFPA fire hazard : 4
NFPA reactivity : 0



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.