

SERVICE PRO® PREMIUM MOTOR OILS

Manufactured with highly refined base oils and licensed additive technology

DESCRIPTION: SERVICE PRO® Premium Motor Oils are formulated to provide engine protection under severe operating conditions. SERVICE PRO® Premium Motor Oils are blended from selected and highly refined base oils compounded to provide protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

SERVICE PRO® Premium Motor Oils may be used over a wide temperature range. They also permit easier cold weather starting and helps minimize engine friction at start-up. API SN PLUS helps prevent pre-ignition and wear, and provides improved cleanliness and fuel economy.

Recommended for automotive gasoline engines, including those equipped with superchargers, used in passenger cars, light trucks, power boats and other mobile and stationary equipment.

Meets API Service Category SN PLUS, SN, SM, SL, SJ.

PERFORMANCE BENEFITS:

- Resisted breakdown under high temperatures
- Maintained oil pressure under heavy load conditions
- Minimized rust and corrosion
- Good low temperature pour point

TYPICAL PROPERTIES*:

SAE Grade	10W40	20W50
Viscosity		
@40 Deg. C, cSt	100.5	165
@100 Deg. C, cSt	14.1	18
Viscosity Index	144	120
Sulfated Ash, %wt.	<1.0	<1.0
Pour Point Deg. F	-30	-27



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



SPWNPCMO

Updated: 04/18

SERVICE PRO® PREMIUM SINGLE GRADE MOTOR OILS

Manufactured with highly refined base oils and licensed additive technology

DESCRIPTION: SERVICE PRO® Premium Single Grade Motor Oils are formulated to provide engine protection under severe operating conditions. Made from selected and highly refined base oils compounded to provide protection against wear and corrosion, they help prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

SERVICE PRO® Premium Single Grade Motor Oils are recommended for all major automotive gasoline and LPG powered engines for passenger cars, pickup trucks, vans and SUV's. Meets current API licensing Service Category SN PLUS, as well as former API Classifications SN, SM, SL, SJ, SH. SERVICE PRO® Premium Single Grade Motor Oils are especially recommended for use in automotive applications involving high temperatures and type service such as hauling boats and camping trailers at sustained high speeds for long periods of time. In all cases, the car or engine manufacturer's lubricant recommendations for API performance category and SAE viscosity grade should be followed.

TYPICAL PROPERTIES*:	SAE Grade	30	40
API Gravity		28.4	27.5
Pounds per gallon		7.37	7.42
Pour point, Deg. F		-18	-12
Viscosity			
40 Deg C, cSt		97.85	129.3
100 Deg C, cSt		11.6	13.9
Viscosity Index		107	104
Flash Point Deg. F		400	400
Sulfated Ash, % wt.		<1.0	<1.0



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.