

# SERVICE PRO FUEL INJECTOR AIR-INTAKE CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 05/28/2014

Revision date: 05/28/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : SERVICE PRO FUEL INJECTOR AIR-INTAKE CLEANER  
Product code : SP2412

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel injector intake cleaner.

#### 1.3. Details of the supplier of the safety data sheet

The Penray Companies, Inc.  
440 Denniston Ct.  
Wheeling, IL 60090  
T (800) 373-6729

Manufactured for:  
AIOD  
P.O. Box 1861  
Montrose, CO 81402  
970-240-4176

#### 1.4. Emergency telephone number

Emergency number : (800) 373-6729  
CHEMTREC (800) 424-9300  
CHEMTREC International +1 (703) 527-3887 24 hr

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable Aerosol 1  
Gases Under Pressure - Liquefied gas  
Skin irritation 2  
Eye irritation 2A  
Carcinogenicity 2  
Reproductive toxicity 2 (developmental)  
Specific target organ toxicity - Single exposure 3  
Specific target organ toxicity - Repeated exposure 2  
Aspiration hazard 1

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### 2.3. Other hazards

No additional information available

# SERVICE PRO FUEL INJECTOR AIR-INTAKE CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Acetone	(CAS No) 67-64-1	30 - 60	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3
Propane	(CAS No) 74-98-6	7 - 13	Flam. Gas 1 Liquefied gas
Toluene	(CAS No) 108-88-3	7 - 13	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Repr. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1
Butane	(CAS No) 106-97-8	5 - 10	Flam. Gas 1 Liquefied gas
2-Butoxyethanol	(CAS No) 111-76-2	5 - 10	Flam. Liq. 3 Acute Tox. 4 (Oral, Dermal, Inhalation) Skin Irrit. 2 Eye Irrit. 2A
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	3 - 7	Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2
Phenylethane	(CAS No) 100-41-4	0.5 - 2	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Carc. 2

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation. Intentional misuse of product by inhalation can result in asphyxiation or death.
- Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

# SERVICE PRO FUEL INJECTOR AIR-INTAKE CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

### 6.2. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/mist/vapors/spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50°C/ 122°F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Propane (74-98-6)		
USA ACGIH	ACGIH TWA (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

Butane (106-97-8)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm

2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm

# SERVICE PRO FUEL INJECTOR AIR-INTAKE CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Phenylethane (100-41-4)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas/Pressurized Liquid.
Appearance	: Clear.
Colour	: Colourless.
Odour	: Solvent.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: No data available.
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 0.872 - 0.877
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

# SERVICE PRO FUEL INJECTOR AIR-INTAKE CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 10.2. Chemical stability

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

### 10.5. Incompatible materials

Acids. Amines. Bases. Oxidizers.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

SP2412	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5 mg/l/4h

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LC50 inhalation rat (mg/l)	50100 mg/m <sup>3</sup> /8h

Propane (74-98-6)	
LC50 inhalation rat (mg/l)	658 mg/l/4h

Toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	12124 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	28.1 mg/l/4h

Butane (106-97-8)	
LC50 inhalation rat (mg/l)	658 mg/l/4h

2-Butoxyethanol (111-76-2)	
LD50 oral rat	470 mg/kg
LC50 inhalation rat (ppm)	450 ppm/4 h

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	>1700 mg/kg
LC50 inhalation rat (mg/l)	47635 mg/l/4h

Phenylethane (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.  
Germ cell mutagenicity : Based on available data, the classification criteria are not met.  
Carcinogenicity : Suspected of causing cancer.

Toluene (108-88-3)	
IARC group	3

2-Butoxyethanol (111-76-2)	
IARC group	3
National Toxicity Program (NTP) Status	1

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3

# SERVICE PRO FUEL INJECTOR AIR-INTAKE CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Phenylethane (100-41-4)	
IARC group	2B
National Toxicity Program (NTP) Status	1

Reproductive toxicity	: Suspected of damaging the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation. Intentional misuse of product by inhalation can result in asphyxiation or death.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

### 12.2. Persistence and degradability

SP2412	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

SP2412	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapours may accumulate in the container. Do not incinerate closed containers.

## SECTION 14: Transport information

In accordance with DOT:

### 14.1. UN number

UN-No. UN1950

### 14.2. UN proper shipping name

Proper Shipping Name : Aerosols, flammable  
Hazard Classes 2.1  
Hazard labels :



### 14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

# SERVICE PRO FUEL INJECTOR AIR-INTAKE CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### Propane (74-98-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 %

### Butane (106-97-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 %

### Phenylethane (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 0.1 %

## 15.2. US State regulations

### SP2412

State or local regulations


This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

IARC	International Agency for Research on Cancer.
	1 - Carcinogenic to humans; 2A - Probably carcinogenic to humans; 2B - Possibly carcinogenic to humans; 3 - Not classifiable; 4 - Probably not carcinogenic to humans.
NTP	National Toxicology Program.
	1 - Evidence of Carcinogenicity; 2 - Known Human Carcinogens; 3 - Reasonably anticipated to be Human Carcinogen; 4 - Substances delisted from report on Carcinogens; 5 - Twelfth Report - Items under consideration.

## SECTION 16: Other information

Indication of changes	:	None.
Date of issue	:	05/28/2014
Other information	:	None.
NFPA health hazard	:	2
NFPA fire hazard	:	4
NFPA reactivity	:	0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

# SERVICE PRO FUEL INJECTOR CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 12/31/2014

Revision date: 12/31/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : SERVICE PRO FUEL INJECTOR CLEANER  
Product code : SP9112

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel System cleaner.

#### 1.3. Details of the supplier of the safety data sheet

The Penray Companies, Inc.  
440 Denniston Ct.  
Wheeling, IL 60090  
T (800) 373-6729

Manufactured for:  
AIOD  
P.O. Box 1861  
Montrose, CO 81402  
970-240-4176

#### 1.4. Emergency telephone number

Emergency number : (800) 373-6729  
CHEMTREC (800) 424-9300  
CHEMTREC International +1 (703) 527-3887 24 hr

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable Liquid 2  
Skin irritation 2  
Carcinogenicity 2  
Specific target organ toxicity - Single exposure 3  
Aspiration hazard 1

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces.– No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS-US)

4 percent of the mixture consists of ingredient(s) of unknown acute toxicity.



# SERVICE PRO FUEL INJECTOR CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Kerosene, petroleum	(CAS No) 8008-20-6	60 - 100	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Polyolefin alkyl phenol alkyl amine	Proprietary	1 - 2	Skin Irrit. 2 Eye Irrit. 2A
Pseudocumene	(CAS No) 95-63-6	0.5 - 1.5	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Naphthalene	(CAS No) 91-20-3	< 0.5	Acute Tox. 4 (Oral) Carc. 2

\* The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.
- Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

#### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

# SERVICE PRO FUEL INJECTOR CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### 6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Kerosene, petroleum (8008-20-6)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>

Polyolefin alkyl phenol alkyl amine (Proprietary)	
ACGIH	Not applicable
OSHA	Not applicable

Pseudocumene (95-63-6)	
ACGIH	Not applicable
OSHA	Not applicable

Naphthalene (91-20-3)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm

### 8.2. Exposure controls

- Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear chemically resistant protective gloves.
- Eye protection : Safety glasses or goggles are recommended when using product.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Environmental exposure controls : Maintain levels below Community environmental protection thresholds.
- Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

# SERVICE PRO FUEL INJECTOR CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear
Color	: Amber
Odor	: Petroleum odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 22 °C (71 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.864 - 0.869
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

#### 10.4. Conditions to avoid

Heat. Incompatible materials. Open flame.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

SP9112	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	No data available
Kerosene, petroleum (8008-20-6)	
LD50 oral rat	> 5000 mg/kg

# SERVICE PRO FUEL INJECTOR CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

<b>Kerosene, petroleum (8008-20-6)</b>	
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h

<b>Pseudocumene (95-63-6)</b>	
LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	18 g/m <sup>3</sup> /4h

<b>Naphthalene (91-20-3)</b>	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	> 20 g/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Suspected of causing cancer.

<b>Naphthalene (91-20-3)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	---

### 12.2. Persistence and degradability

<b>SP9112</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>SP9112</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming	: No known ecological damage caused by this product.
------------------------------	--

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additional information	: Handle empty containers with care because residual vapors are flammable.

# SERVICE PRO FUEL INJECTOR CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### SECTION 14: Transport information

In accordance with DOT

UN-No.(DOT) : UN1993  
Proper Shipping Name (DOT) : Flammable liquids, n.o.s. (Petroleum, Pseudocumene)  
Department of Transportation (DOT) Hazard Classes : 3  
Hazard labels (DOT) :



Packing group (DOT) : II

### Additional information

Other information : No supplementary information available.  
Special transport precautions : Do not handle until all safety precautions have been read and understood.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

#### Pseudocumene (95-63-6)

Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

#### Naphthalene (91-20-3)

Listed on United States SARA Section 313

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
--------------------------	--

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

#### 15.2. US State regulations


#### SP9112

State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	---

### SECTION 16: Other information

Indication of changes : None.  
Date of issue : 12/31/2014  
Other information : None.

NFPA health hazard : 2  
NFPA fire hazard : 3  
NFPA reactivity : 0



*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*

# SERVICE PRO INTAKE VALVE DEPOSIT CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 07/24/2014

Revision date: 07/24/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : SERVICE PRO INTAKE VALVE DEPOSIT CLEANER  
CAS No : SP9312

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel System cleaner.

#### 1.3. Details of the supplier of the safety data sheet

The Penray Companies, Inc.  
440 Denniston Ct.  
Wheeling, IL 60090  
T (800) 373-6729

Manufactured for:  
AIOD  
P.O. Box 1861  
Montrose, CO 81402  
970-240-4176

#### 1.4. Emergency telephone number

Emergency number : (800) 373-6729  
CHEMTREC (800) 424-9300  
CHEMTREC International +1 (703) 527-3887 24 hr

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable Liquid 2  
Acute toxicity 4 (Dermal, Inhalation)  
Skin irritation 2  
Carcinogenicity 2  
Reproductive toxicity 2 (developmental)  
Specific target organ toxicity - Repeated exposure 2  
Aspiration hazard 1

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Highly flammable liquid and vapor. Harmful in contact with skin or if inhaled. Causes skin irritation. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces.— No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### 2.3. Other hazards

No additional information available

# SERVICE PRO INTAKE VALVE DEPOSIT CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	60 - 100	Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2
Phenylethane	(CAS No) 100-41-4	7 - 30	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2 Asp. Tox. 1
Toluene	(CAS No) 108-88-3	7 - 13	Flam. Liq. 2 Skin Irrit. 2 Repr. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	0.5 - 1.5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A Asp. Tox. 1

\* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Harmful if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : Harmful in contact with skin. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

#### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

# SERVICE PRO INTAKE VALVE DEPOSIT CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

#### 6.2. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

#### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not breathe gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.

#### 7.3. Specific end use(s)

Not available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Phenylethane (100-41-4)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

Solvent naphtha, petroleum, light aromatic (64742-95-6)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

#### 8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Safety glasses or goggles are recommended when using product.



# SERVICE PRO INTAKE VALVE DEPOSIT CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Appearance	: Clear.
Color	: Amber.
Odor	: Petroleum odor.
Odor threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: ~ 22 °C (~ 71 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapor pressure	: No data available.
Relative vapor density at 20 °C	: No data available.
Relative density	: 0.864 - 0.869
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Heat. Incompatible materials. Open flame.

### 10.5. Incompatible materials

Acids. Bases. Strong oxidizing agents.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful in contact with skin or if inhaled.

# SERVICE PRO INTAKE VALVE DEPOSIT CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SP9312

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	>1000 but ≤2000 mg/kg
LC50 inhalation rat	>10.0 but ≤20.0 mg/l/4h (Calculated using ATE values)

### Xylenes (o-, m-, p- isomers) (1330-20-7)

LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	> 1700 mg/kg
LC50 inhalation rat	5000 ppm/4 h

### Phenylethane (100-41-4)

LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat	17.2 mg/l/4h

### Toluene (108-88-3)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	12124 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat	28.1 mg/l/4h

### Solvent naphtha, petroleum, light aromatic (64742-95-6)

LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	3400 ppm/4h
LC50 inhalation rat	> 5.2 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Suspected of causing cancer.

### Xylenes (o-, m-, p- isomers) (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

### Phenylethane (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

### Toluene (108-88-3)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Suspected of damaging the unborn child.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Harmful in contact with skin. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	---

# SERVICE PRO INTAKE VALVE DEPOSIT CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 12.2. Persistence and degradability

#### SP9312

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### SP9312

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer : No additional information available  
Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.  
Additional information : Handle empty containers with care because residual vapors are flammable.

## SECTION 14: Transport information

In accordance with DOT

### 14.1. UN number

UN-No. : 3295

### 14.2. UN proper shipping name

Proper Shipping Name : Hydrocarbons, liquid, n.o.s. (Xylene, Phenylethane, Toluene)  
Department of Transportation Hazard Classes : 3  
Hazard labels :



Packing group : II

### 14.3. Additional information

Other information : No supplementary information available.  
Special transport precautions : Do not handle until all safety precautions have been read and understood.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

#### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

#### Phenylethane (100-41-4)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

#### Toluene (108-88-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

### 15.2. US State regulations

# SERVICE PRO INTAKE VALVE DEPOSIT CLEANER

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.


### SP9312

State or local regulations

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

### SECTION 16: Other information

Indication of changes : None.  
Date of issue : 07/24/2014  
Other information : None.  
NFPA health hazard : 2  
NFPA fire hazard : 3  
NFPA reactivity : 0



*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*