

SERVICE PRO® PREMIUM MOTOR OILS

Manufactured with highly refined base oils and licensed additive technology

DESCRIPTION: SERVICE PRO® Premium Motor Oils are formulated to provide engine protection under severe operating conditions. These oils are formulated with highly refined base oils and additives to provide protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

SERVICE PRO® Premium Motor Oils meet API SP to help prevent low speed pre-ignition, internal engine parts wear and provide improved cleanliness and fuel economy. Recommended for automotive gasoline engines, including those equipped with superchargers, used in passenger cars, light trucks, power boats and other mobile and stationary equipment. Always follow manufacturer's recommendations for viscosity grade and API Service Category.

- PERFORMANCE BENEFITS:**
- Meets:
- API Service Category : SP, SN PLUS, SN, SM, SL, SJ
 - Resists breakdown under high temperatures
 - Maintains oil pressure under heavy load conditions
 - Minimizes rust and corrosion
 - Good low temperature pour point

TYPICAL PROPERTIES*:

		API SP 10W-40	API SP 20W-50
SAE Grade			
Kinematic Viscosity @ 100°C (cSt)	ASTM D445	14.7	18.1
Kinematic Viscosity @ 40°C (cSt)	ASTM D445	100.1	163.8
Viscosity Index		153	123
NOACK Volatility, Mass %	ASTM D5800	12	4
Specific Gravity		0.872	0.881
API Gravity		30.8	29.1
Pour Point, °F	ASTM D97	-30	-25
Phosphorus, mass %	ASTM D4951	0.07	0.07



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



SERVICE PRO® PREMIUM SINGLE GRADE MOTOR OILS

Manufactured with highly refined base oils and licensed additive technology

DESCRIPTION: SERVICE PRO® Premium Single Grade Motor Oils are formulated to provide engine protection under severe operating conditions. Manufactured from highly refined base oils and additives, these oils provide protection against wear and corrosion, and help to prevent oxidative thickening, inhibit promotion of engine acids, sludge and reduce varnish deposits.

SERVICE PRO® Premium Single Grade Motor Oils are recommended for all major automotive gasoline and LPG powered engines for passenger cars, pickup trucks, vans and SUV's. Meets current API licensing Service Category SP, as well as former API Classifications SN-Plus, SN, SM, SL, SJ, SH. SERVICE PRO® Premium Single Grade Motor Oils are especially recommended for use in automotive applications involving high temperatures and high speeds for extended periods. Always follow manufacturer's recommendations for viscosity grade and API Service Category.

TYPICAL PROPERTIES*:

		API SP	API SP
SAE Grade		30	40
Kinematic Viscosity @ 100°C (cSt)	ASTM D445	9.9	12.9
Kinematic Viscosity @ 40°C (cSt)	ASTM D445	75.9	115.2
Viscosity Index		111	105
NOACK Volatility, Mass %	ASTM D5800	6	4
Specific Gravity		0.876	0.881
API Gravity		30.0	29.1
Pour Point, °F	ASTM D97	-26	-25
Phosphorus, mass %	ASTM D4951	0.07	0.07



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Revised 04/2020

SPCOSGPCMO

