

# SERVICE PRO<sup>®</sup> PREMIUM HI-TEMP EP-2 LITHIUM COMPLEX GREASE

Formulated for high temp wheel bearing applications

**DESCRIPTION:** SERVICE PRO<sup>®</sup> Premium High-Temp Grease is an exceptionally versatile multi-purpose grease that provides superior protection to lubricate a wide variety of severe duty automotive, trucking, industrial, mining and construction equipment. SERVICE PRO<sup>®</sup> Premium High-Temp Grease contains extreme pressure (EP) additives to minimize wear in heavily-loaded components and is suitable for use at higher temperatures than conventional greases. This grease satisfies a wide range of industrial and automotive applications including wheel bearings, ball joints and bushings.

**PERFORMANCE BENEFITS:**

- Premium quality lithium complex multi-purpose grease
- Fully additive treated: EP/anti-wear, rust and oxidation inhibited
- Highly water resistant
- Superior disc brake wheel bearing and chassis performance
- Meets the requirements of NLGI Service Classification GC-LB

**TYPICAL PROPERTIES\*:**

NLGI Consistency Number	2
Thickener	Lithium Complex
Texture	Smooth, Tacky
Color, Observed	Red
Base Oil Viscosity, cSt @ 40°C	220
Worked 60 Penetration, D-217	265 - 295
Dropping Point, D-566, °F. (°C.)	500 (260)
Wheel Bearing Leakage, D-4290, g loss	2
Timken EP Test, OK Load, lbs	80+
Water Washout, D-1264, % loss	2.5 @ 175° F
Rust Prevention, D-1743, rating	Pass
Oil Separation, D-1742, % loss	1
Four-Ball Wear, D2266, mm	0.45
Four-Ball EP Weld Point, D-2596, kgf	315
Four-Ball Load Wear Index, D-2596, kgf	50

\*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



Revised 07/2019  
SPHTG