SERVICE PRO® PREMIUM SYNTHETIC BLEND MOTOR OILS

<u>Service pr</u>

Manufactured with highly refined base oils and licensed additive technology

DESCRIPTION: SERVICE PRO[®] Premium Synthetic Blend Motor Oils are premium performance automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. Manufactured with a blend of full synthetic and high viscosity index Group II base oils combined with an industry leading additive package to ensure maximum protection against wear, rust, corrosion, oxidative thickening, acid formation and sludge. This formulation protects against low speed pre-ignition and chain wear found in late model engines, while maximizing fuel economy. Always follow manufacturer's recommendations for viscosity grade and API Service Category.

PERFORMANCE: SERVICE PRO[®] Premium Synthetic Blend Motor Oils meet or exceed the requirements of:

- API SP Resource Conserving /ILSAC GF-6A
- API Service Category: SP, SN PLUS, SN, SM, SL, SJ
- Ford WSS-M2C960-A1 (SAE 5W-20), WSS-M2C961-A1 (SAE 5W-30)
- Ford WSS-M2C945-A/B1 (SAE 5W-20), WSS-M2C946-A/B1 (SAE 5W-30)
- Toyota Service Fill Specifications
- Honda Service Fill Specifications
- Mazda Service Fill Specifications
- FCA Chrysler MS-6395
- GM 6094M (for applicable grades)

TYPICAL PROPERTIES*:

| | | API SP-RC | API SP-RC | API SP-RC |
|-----------------------------------|------------|-------------|-------------|-------------|
| | | ILSAC GF-6A | ILSAC GF-6A | ILSAC GF-6A |
| SAE Grade | | 5W-20 | 5W-30 | 10W-30 |
| Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 8.5 | 10.3 | 10.1 |
| Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 48.5 | 60.3 | 64.1 |
| Viscosity Index | | 153 | 160 | 143 |
| NOACK Volatility, Mass % | ASTM D5800 | 11 | 12 | 12 |
| Specific Gravity | | 0.856 | 0.856 | 0.867 |
| API Gravity | | 33.6 | 33.6 | 31.7 |
| Pour Point, °F | ASTM D97 | -35 | -35 | -35 |
| Phosphorus, mass % | ASTM D4951 | 0.07 | 0.07 | 0.07 |

*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Revised 04/2020 SPWNSYNB



