

Safety Data Sheet

Issue Date: 02-Sept.-2014

Reviewed Date: 25- Feb-2021

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Service Pro EP2 Lithium Grease

Other means of identification

SDS # SP-037, SPL17054, SPL27054, SPL37054, SPL00260, SPL00261, SPL00270, SPL00271

Recommended use of the chemical and restrictions on use

Recommended Use Lubricating grease

Details of the supplier of the safety data sheet

Supplier Address

Warren Oil Company
915 E. Jefferson Ave.
West Memphis, AR 72301

Manufactured for:

AIOD
P.O. BOX 1861
Montrose, CO 81402-1861
970-249-6336 www.service-pro.com

Emergency Telephone Number

Company Phone Number 1-800-428-9284
Emergency Telephone (24 hr) CHEMTREC 1-800-424-9300 (North America) 1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Appearance: Dark Amber

Physical State: Semi-solid to solid

Odor: Mild petroleum

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2

Signal Word

Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation



Precautionary Statements – Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements – Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing if eye irritation persists: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash it before reuse
 If skin irritation occurs: Get medical advice/attention

Other Hazards

Harmful to aquatic life with long lasting effects

Unknown Acute Toxicity

2.25% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Severely Hydrotreated Heavy Naphthenic Petroleum Oil	64742-52-5	70-80
Residual oils (petroleum), hydrotreated	64742-57-0	1-10
Zinc Alkyl Dithiophosphate	68649-42-3	<5
Lithium Hydroxide Solution	1310-66-3	<5
Petroleum Asphalt	8052-42-4	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

- Eye Contact** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Skin Contact** Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
- Inhalation** Vaporization is not expected at ambient temperatures. This material is not expected to cause inhalation-related disorders under anticipated conditions of use. In case of overexposure, move the person to fresh air.
- Ingestion** DO NOT induce vomiting unless directed by a physician. Rinse out mouth with water. Never give anything by mouth to a person who is not fully conscious. Allow small quantities to pass through the digestive system. If large amounts are swallowed or irritation of discomfort, seek medical attention immediately.

Most important symptoms/effects

- Symptoms** Causes skin irritation. Causes serious eye irritation. No significant adverse health effects are expected to occur upon short term exposure at ambient temperatures. At elevated temperatures, product vapor may cause respiratory tract irritation. Repeated or prolonged overexposure to product mists can result in respiratory tract inflammation and an increased risk of infection. This material can cause a laxative effect. If swallowed in large quantities, this material can obstruct the intestine.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Skin: In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Early symptoms may be minimal. Ingestion: Check for possible bowel obstruction with ingestion of large quantities of material.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing media

Use dry chemical, foam, carbon dioxide or water fog.

Unsuitable extinguishing media Not determined.

Specific Hazards Arising from the Chemical

Water or foam may cause frothing. Carbon dioxide and inert gas can displace oxygen. Use caution when applying carbon dioxide or inert gas in confined spaces.

Hazardous Combustion Products Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur, phosphorus, zinc and/or zinc.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight the fire from a safe distance in a protected location. Open any masses with a water stream to prevent re-ignition due to smoldering. Cool surface with water fog. Molten material can form flaming droplets if ignited. Use of water on product above 100°C (212°F) can cause product to expand with explosive force. Do not allow liquid runoff to enter sewers or public waters.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazard; do not walk through spilled material.

Environmental Precautions See Section 12 for additional Ecological Information. Prevent entry into waterways or sewers.

Methods and material for containment and cleaning up

Methods for Containment Stop leak if you can do so without risk.

Methods for Clean-Up For small spills, absorb or cover with dry earth, sand or other inert non-combustible absorbent material and place in to waste containers for lateral disposal. Contain large spills to maximize product recovery or disposal. In urban area, clean up spill as soon as possible. In natural environments, seek clean up advice from specialists to minimize physical habitat damage. This material will float on water. Absorbent pads and similar materials can be used.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wash face, hands, and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Avoid water contamination and elevated temperatures to minimize product degradation. Empty containers may contain product residue that can ignite with explosive force. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. Keep container tightly closed. Store in a cool, dry, well-ventilated area. Store only in approved containers. Do not store with strong oxidizing agents. Do not store at elevated temperatures. Avoid storing product in direct sunlight for extended periods of time.

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Severely Hydrotreated Heavy Naphthenic Petroleum Oil 64742-52-5	TWA: 5 mg/m ³ (oil mist) STEL: 10 mg/m ³ (oil mist)	TWA: 5 mg/m ³ (oil mist) STEL: none estab.	TWA: none estab. STEL: none estab.
Petroleum Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m ³ fume 15 min

Appropriate engineering controls

Engineering Controls Ventilation controls are not normally required under anticipated conditions of use. Provide exhaust ventilation or other engineering controls if airborne mists or vapors concentrations exceed recommended occupational exposure limits listed. An eye wash station and safety shower should be located near work station.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses equipped with side shields are recommended as a minimum protection in industrial settings. Wear goggles if splashing or spraying is anticipated. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available.

Skin and Body Protection Use gloves constructed of chemical resistant materials such as heavy nitrile rubber if frequent or prolonged contact is expected. Use heat-protective gloves when handling product at elevated temperatures. Use clean protective clothing if splashing or spraying conditions are present. Protective clothing may include long-sleeve outer garment, apron, or lab coat. If significant contact occurs, remove oil-contaminated clothing as soon as possible and promptly shower. Launder contaminated clothing before reuse or discard. Wear heat protective boots and protective clothing when handling material at elevated temperatures.

Respiratory Protection The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Semi-solid to solid	Odor	Mild petroleum
Appearance	Dark Amber	Odor Threshold	Not determined
Color	Dark Amber		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not available	
Melting Point/Freezing Point	Not available	
Boiling Point/Boiling Range	Not available	
Flash Point	238 °C / 460 °F	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not available	@ 20°C (68°F)
Lower Flammability Limits	Not available	(Air = 1)
Vapor Pressure	<0.001 kPa (<0.01 mmHg)	(Water = 1)
Vapor Density	>10	
Specific Gravity	<1	
Water Solubility	Negligible solubility in cold water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not available	
Decomposition Temperature	Not determined	
Kinematic Viscosity	187 cSt	@ 40°C (104°F)
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Not expected to occur.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur, phosphorus, zinc and/or nitrogen.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Causes skin irritation.

Inhalation Do not inhale.

Ingestion Do not ingest.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrotreated Castor Oil – (flake or solid) 8001-78-3	> 10 g/kg (Rat)	-	-
Lithium Hydroxide Solution 1310-66-3	= 120 mg/kg (Rat)	-	= 0.96 mg/L (Rat) 4 h
Petroleum Asphalt 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms Please see Section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Numerical measures of toxicity

Not determined

Unknown Acute Toxicity 2.25% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Severely Hydrotreated Heavy Naphthenic Petroleum Oil 64742-52-5		5000: 96 h Onocorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Hydrogenated Castor Oil – (flake or solid) 8001-78-3		10000: 96 h Brachydanio rerio mg/L LC50		
Zinc Alkyl Dithiophosphate 68649-42-3		1.0 – 5.0: 96 h Pimepphales promelas mg/L LC50 static 10.0 – 35.0: 96 h Pimepphales promelas mg/L LC50 semi-static		1 – 1.5: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Petroleum Asphalt 8052-42-4	>6

Other adverse effects

Not determined.

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

- Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Zinc Alkyl Dithiophosphate 68649-42-3	Toxic

14. TRANSPORT INFORMATION

- Note** Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
- DOT** Not regulated
- IATA** Not regulated
- IMDG** Not regulated

15. REGULATORY INFORMATION

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Severely Hydrotreated Heavy Naphthenic Petroleum Oil	Present	X		Present		Present	X	Present	X	X
Residual oils (petroleum), hydrotreated	Present	X		Present		Present	X	Present	X	X
Zinc Alkyl Dithiophosphate	Present	X		Present			X	Present	X	X
Lithium Hydroxide Solution						Present	X		X	X
Petroleum Asphalt	Present	X		Present		Present	X	Present	X	X

Legend:

- TSCA – United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL – Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS – European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS – Japan Existing and New Chemical Substances*
- IECSC – China Inventory of Existing Chemical Substances*
- KECL – Korean Existing and Evaluated Chemical Substances*
- PICCS – Philippines Inventory of Chemicals and Chemical Substances*
- AICS - Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 – Threshold Values %
Zinc Alkyl Dithiophosphate – 68649-42-3	68649-42-3	<5	1.0

CWA (Clean Water Act)

Chemical Name	CWA – Reportable Quantities	CWA – Toxic Pollutants	CWA – Priority Pollutants	CWA – Hazardous Substances
Zinc Alkyl Dithiophosphate		X		

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Zinc Alkyl Dithiophosphate 68649-42-3	X		X
Lithium Hydroxide Solution 1310-66-3	X		
Petroleum Asphalt 8052-42-4	X	X	X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
HMIA	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	1	0	Not determined

Issue Date: 02-Sept.-2014
 Review Date: 25-Feb.-2021
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet