

SERVICE PRO® PREMIUM SYNTHETIC BLEND HIGH MILEAGE MOTOR OILS

Manufactured with highly refined base oils and licensed additive technology

DESCRIPTION: SERVICE PRO® Premium Synthetic Blend High Mileage API SP Motor Oils are formulated to provide engine protection for vehicles with 75,000 miles or greater. These oils are blended from highly refined synthetic and conventional base oils combined with industry leading additives. This formulation provides protection against wear and corrosion, prevent oxidative thickening and inhibits promotion of engine acids, sludge and varnish deposits. API SP helps to prevent low speed pre-ignition and chain wear, while providing improved cleanliness and fuel economy. These advanced formula motor oils are designed for high mileage vehicles that may be experiencing an increase in oil consumption or an increase in leakage. Always follow manufacturer's recommendations for viscosity grade and API Service Category.

PERFORMANCE: SERVICE PRO® Premium Synthetic Blend Motor Oils meet or exceed the requirements of:

BENEFITS:

- API SP Resource Conserving /ILSAC GF-6A
- API Service Category: SP, SN PLUS, SN, SM, SL, SJ
- Ford WSS-M2C960-A1 (SAE 5W-20), WSS-M2C961-A1 (SAE 5W-30)
- Ford WSS-M2C945-A/B1 (SAE 5W-20), WSS-M2C946-A/B1 (SAE 5W-30)
- Toyota Service Fill Specifications
- Honda Service Fill Specifications
- Mazda Service Fill Specifications
- FCA Chrysler MS-6395
- GM 6094M (for applicable grades)

**TYPICAL
PROPERTIES*:**

		API SP-RC ILSAC GF-6A	API SP-RC ILSAC GF-6A	API SP-RC ILSAC GF-6A	API SP
		5W-20	5W-30	10W-30	10W-40
SAE Grade		5W-20	5W-30	10W-30	10W-40
Kinematic Viscosity @ 40°C (cSt)	ASTM D445	48.8	59.5	66.3	99
Kinematic Viscosity @ 100°C (cSt)	ASTM D445	8.5	10.1	10.2	14.6
Viscosity Index		152	157	140	153
NOACK Volatility, Mass %	ASTM D5800	11	12	12	12
Specific Gravity		0.857	0.857	0.867	0.868
API Gravity		33.6	33.6	31.7	35.1
Pour Point, °F	ASTM D97	-35	-35	-35	-30
Phosphorus, mass %	ASTM D4951	0.07	0.07	0.07	0.07



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information

Revised 03/2022

SPWNSYNBHM

