

## SERVICE PRO® DEX-COOL® ANTIFREEZE/COOLANT

### PERFORMANCE BENEFITS:

SERVICE PRO® DEX-COOL® Antifreeze/Coolant is engineered and approved for use in all GM vehicles 1995 and newer. Its orange organic acid technology (OAT) formula meets or exceeds the stringent performance requirements of GM specifications GMW3420 and GM6277M, as well as ASTM D3306 and D4985. SERVICE PRO® DEX-COOL® Antifreeze/Coolant provides excellent protection against temperature extremes, rust, corrosion and premature water pump failure for up to 5 years or 150,000\*. It is free of amines, phosphates, borates, nitrites and silicates and is compatible with all cooling system materials.

When used as directed, SERVICE PRO® DEX-COOL® Antifreeze/Coolant:

- Provides protection against damaging rust and corrosion for all cooling system metals, including aluminum
- Service life of up to 5 years/150,000 miles with a complete cooling system flush and fill
- Free of amines, phosphate, borate, nitrite and silicate
- Available in both Concentrate and Ready to Use Prediluted 50/50 formulas

\*With a complete flush and fill. Always consult owner's manual to determine the specific maintenance and changeover interval recommended for your vehicle.

DEX-COOL® and the dex-cool logo are trademarks of GENERAL MOTORS, LLC and used under license. Service Pro License Identification Number DC-21-7

### TYPICAL PROPERTIES\*:

		Concentrate	Prediluted 50/50	ASTM D3306 Limits
Color		Orange	Orange	Distinctive
Ash Content, mass %	ASTM D1119	<5	<2.5	5 max <sup>1</sup> / 2.5 max <sup>2</sup>
pH	ASTM D1287	8.3 (50% by Volume)	8.3	7.5-11.0
Total water, mass %	ASTM D1123	<5	50	5 max <sup>1</sup>
Specific Gravity	ASTM D1122	1.122	1.066	1.110-1.145 <sup>1</sup> / 1.065 min <sup>2</sup>
Freezing Point °F (°C)	ASTM D1177		-37.8 (-38.8)	-34 (-36.4) max
Boiling Point <sup>3</sup> , °F (°C)	ASTM D1120	325 (162.8)	229 (109)	226 (108) min
Effect on Automotive Finish	ASTM D1882	No Effect	No Effect	No Effect
Chloride, ppm	ASTM D3634	<25	<25	25 max

<sup>1</sup> Concentrate only, <sup>2</sup> Prediluted only, <sup>3</sup> Unpressurized

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



SPDCAF  
Revised 12/2023