# SERVICE PRO®

## **Power Steering Fluid**

### SP2263 & SP2287 Power Steering Fluid

- ✓ Meets specs of GM, Ford, Chrysler and most foreign auto manufacturers
- $\checkmark$  Provides protection against foam, corrosion, and oxidation
- ✓ Protects against wear and slippage
- ✓ Helps stop power steering squeaks



# SERVICE PRO

## **Power Steering Fluid**

### SP3832 Full Synthetic Power Steering Fluid

- ✓ Formulated to meet the specifications of European OEM's
- ✓ Exceeds requirements and is suitable for use in all other vehicles
- Provides exceptional viscosity stability over a wide temperature range
- Excellent anti-wear properties ensure suitability for use as hydraulic fluid in suspension systems



# SERVICE PRO®

## Power Steering Fluid SP3015 Full Synthetic Power Steering Fluid for Honda/Acura

✓ For Use in Honda/Acura Vehicles:

- Honda/Acura P/N 08206-9002A
- Honda PSF-2
- Honda PSF Type S
- Honda PSF Type V systems
- ✓ Stops Squeaks, Guards Against Leaks
- ✓ Exceptional anti-wear properties that help protect system
- ✓ Anti-foam agents help prevent pump cavitation
- ✓ Anti-oxidant properties that help stop the formation of sludge
- ✓ Excellent protection and performance in cold weather



#### **SERVICE PRO® PREMIUM POWER STEERING FLUID**

## **DESCRIPTION:** SERVICE PRO<sup>®</sup> Premium Power Steering Fluid is formulated using premium Group II base oils with advanced chemistry offering excellent protection and performance in all power steering systems. It will provide exceptional anti-wear, anti-corrosion, and anti-oxidation control eliminating pump squeal.

#### PERFORMANCE

- Recommended "top tier" power steering fluid for use in GM, Chrysler and Ford cars and trucks
- **BENEFITS:** Suitable for use in European cars specifying "mineral oil" based fluids
  - Protects and conditions power steering system
  - · Keeps seals pliable and efficient (will not harm seals)
  - Extends power steering system life
  - · Protects against wear and corrosion
  - · Eliminates pump cavitations and slippage

Not recommended for complete fluid replacement in applications requiring the use of fully synthetic hydraulic fluid in the power steering system. NOT INTENDED FOR USE IN AUTOMATIC TRANSMISSIONS.

#### Meets industry specifications and is recommended for service fill replacement in power APPLICATIONS: steering systems requiring vehicle specifications listed below:

Audi PN G002000 (mineral oil base) DaimlerChrysler MS1872 & MS5931F Ford MERCON, Ford M2C138-CJ, M2C33-F, and ESW-M2C128 C&D GM 9985010 Saginaw Power Steering Systems GM DEXRON®, DEXRON® II, II-E, III, III-G\*

Kia - USA sales Mercedes Benz PN 00 989 8803 (mineral oil base) Navistar TMS 6810

Saab PM 30 09 800 Subaru PN K0Z09A0080 Volkswagen TL-VW-570-26 (mineral oil base)

SERVICE PRO

|     | T١ | P  | C  | A  |
|-----|----|----|----|----|
| PRA | PF | RT | ΊĒ | S. |

Viscosity @ 40°C Viscosity @ 100°C SUS @ 104° F SUS @ 210° F Viscosity Index Pour Point ° F Flash Point ° F 32-40 6.8-7.6 150-190 35-45 Min. 140 Max. -40 Min 400 ° F



Updated: 05/13

SPSPPSPB

Association of Independent Oil Distributors • www.service-pro.com • P.O. Box 1861 • Montrose, CO 81402 USA

#### SERVICE PRO<sup>®</sup> PREMIUM FULL SYNTHETIC POWER STEERING FLUID

SERVICE PRO

| <b>DESCRIPTION</b> : | SERVICE PRO <sup>®</sup> Premium Full Synthetic Power Steering Fluid is specially formulated to meet the specifications of European OEM's requiring high technology fluids that enable extended change intervals. |
|----------------------|---|
|                      | This premium synthetic power steering fluid exceeds requirements and is suitable for use in all other vehicles. Honda fluid is recommended for Honda and Acura vehicles.  |

**PERFORMANCE BENEFITS:** SERVICE PRO<sup>®</sup> Premium Full Synthetic Power Steering Fluid provides exceptional viscosity stability over a wide temperature range, with improved flow at low temperatures. Excellent anti-wear properties ensure suitability for use as hydraulic fluid in suspension systems, traction control units and as shock absorber fluid.

**APPLICATIONS:** Suitable for use where the following specifications are required:

| Audi P/N G002000               | Mercedes Benz 236.3, P/N 000 989 88 03        |
|--------------------------------|---|
| Audi P/N G002012               | Mercedes Benz 345.0, P/N 001 989 24 03        |
| Chrysler MS-1872               | Mitsubishi PS Fluid Mitsubishi Diamond SP III |
| Chrysler MS-5931, P/N 04883077 | Nissan PSF II                                 |
| Chrysler MS-9602, ATF+4        | Pentosin CHF 7.1                              |
| Chrysler MS-11655              | Pentosin CHF 11S                              |
| Ford M2C195-A                  | Pentosin CHF 202                              |
| Ford M2C204-A                  | Saab P/N (45) 30 09 800                       |
| GM P/N 89021184                | Saab P/N 30 32 380                            |
| GM 9985010, P/N 1052884        | Subaru P/N K0209A0080                         |
| GM 9985835, P/N 12345866       | Toyota PSF Type EH, P/N 008886-01             |
| Hyundai / Kia PSF-3            | VW P/N G00200                                 |
| Hyundai / Kia PSF-4            | VW P/N G002012                                |
|                                | Volvo P/N 1161529                             |
|                                |   |





Updated: 12/16 SPSPPSFSPB