

# **Antifreeze/Coolant Reference Chart**

#### LIGHT CARS & TRUCKS

Service Pro® **All Makes All Models** Antifreeze/Coolant

Yellow

Ethylene Glycol

Good

Nο

No

Technology

Up to 5 Years/

150.000 Miles









Service Pro® Dex-Cool









Ethylene Glycol

Good

Nο

No

**Dex-Cool Compatible** for GM Vehicles

Up to 5 Years/ 150,000 Miles









**Base** 

**Delivers Longer Engine Life** 

**Nitrites** 

**Silicates** 

**Chemistry** 

Service Intervals\*\*

**General Motors** 

**Chrysler** 

**Ford** 

**Asian Vehicles** 

**European Vehicles** 















Ethylene Glycol

Green

Good

Nο

Low Silicate

Formulated for older Vehicles

Up to 2 Years/ 50.000 Miles

1994 & Older

2001 & Older

2002 & Older

1989 & Older

1989 & Older



## Top Off:

- ✓Enhance system performance
- ✓ Fill overflow tank to max level to rejuvenate your existing antifreeze
- ✓ Requires 1 Gallon of 50/50



## **Drain and Fill:**

- ✓ Refresh system to help stop the spread of corrosion and protect against freeze-up and boil-over
- ✓ With cool engine, open drain valve to empty and refill to indicated level
- **✓**Requires 2 Gallons of 50/50



### Flush and Fill:

- ✓ Completely rejuvenate entire cooling system, stopping corrosion and providing ultimate freeze-up and boil-over protection
- ✓ Flush according to directions. Add half the volume of the cooling system with Concentrate. Top off with distilled water until full.
- **✓** Requires 1-2 Gallons of Concentrate Antifreeze

All products available in concentrate and 50/50