

SERVICE PRO® GLOBAL FULL SYNTHETIC MULTI-VEHICLE ATF

Manufactured with highly refined base oils and industry leading additive chemistry

DESCRIPTION:

SERVICE PRO® Global Full Synthetic Multi-Vehicle ATF represents the latest technology in full synthetic automatic transmission fluids. It is specifically formulated for the newest generation of high efficiency transmissions and is also a fuel efficient choice for older models as well.

SERVICE PRO® Global Full Synthetic Multi-Vehicle ATF meets the requirements of JASO M315-2013 1A-LV specification. Also suitable for use in many applications including many General Motors, Ford, FCA/Chrysler, Toyota/Lexus/ Scion (T-III, IV, WS), Nissan/Infiniti (Matic D, J, K, S, W), and Honda/Acura (ATF Z-1, DW-1) transmissions, as well as transmissions installed in Hyundai/ Kia (SP-II, III, IV, Red-1K), Isuzu (SCS, ATF II, III), Jaguar, Land Rover, Mazda(F-1, FZ, M-III, T-IV, MV), Mercedes-Benz (236.10, 236.3, 236.5, 236.6, 236.7, 236.9, 236.15), Mitsubishi (Diamond SP, II, III, ATF J2, J3), Porsche, BMW(LA2634, LT71141), MINI, SAAB, Subaru (HP), Suzuki, Volvo and VW/Audi (09A, 09G) cars and light trucks. It is also suitable for transfer case applications calling for Ford XL-12 fluid.

This product is NOT recommended for Ford Type F, Continuously Variable Transmissions (CVT) or Double Clutch Transmissions (DCT) which require specialized OEM fluids. Check owner’s manual for specific recommendations.

PERFORMANCE BENEFITS:

- Improved oxidation and thermal stability
- Full synthetic formula
- Outstanding low temperature performance
- Superior anti-wear protection
- Improved torque transfer

Note: This product is not for sale or use in the State of California.

TYPICAL PROPERTIES*:

API Gravity	34.8
Sp. Gr. @ 60° F	0.8468
Flash. COC. ° F	400
Pour Pt.. ° F	-55
Viscosity. cP @ -40 °C	12100
Viscosity, cSt @ 40 °C	32
cSt @ 100 °C	6.3
Viscosity Index	152
Color	Red

* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



SERVICE PRO® GLOBAL FULL SYNTHETIC MULTI-VEHICLE ATF

Manufactured with highly refined base oils and industry leading additive chemistry

Service Pro Global Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:

OEM/ ATF	APPLICATION	OEM/ ATF	APPLICATION	
AISIN	AW-2		Fiat 9.55550-AV5	
	JWS 3309 ATF, ATF-0T4		Fiat 9.55550-AV6	
	JWS 3324 ATF, ATF-0WS		MB 236.10/12, P/N 05127382AA	
Allison	C2		P/N 05127382	
	C3		P/N 68157995AA/AB	
	C4		P/N 68333587AA	
ATF	134	FCA continued	SP-4, P/N 68171866AA	
	3353		SP-III	
	3100.PL085		SP-IV, P/N 68171866AA	
	3403-M115		SP-IV, P/N 68171869AA	
	D971		Type 7176E	
	ETL-7045 E		Type 9602	
	K17			
	L12108		ESP-M2C138-CJ	
	LA 2634		ESP-M2C166-H	
	M-1375.4		P/N XT-10-QLV [LV], XT-10-QLVC	
	M-1375.6		P/N XT-12-ULV [ULV]	
	N402		P/N XT-2-QDX [M]	
	SP-III		P/N XT-2-QSM [Syn]	
Bentley	P/N PY112995PA	Ford	P/N XT-5-QM [V]	
	ATF 3+		P/N XT-5-QSM [V Syn]	
ATF 7	P/N XT-6-QSP [SP]			
ATF4	P/N XT-8-QAW [Premium]			
ATF6	P/N XT-9-QMM5 [FNR5]			
ETL-7045 and ETL-7045 E	Spec WSS-M2C922-A1			
ETL-8072B				
LA 2634	ATF Z1, Saturn P/N 22717466			
LT 71141	AW-1, P/N 19256039			
M-L12108	Dex [GM 6032M]Dex ULV, P/N 19352619			
P/N 81 22 9 400 272/275	Dex-B [GM 6032M]			
P/N 81 22 9 407 858/859	Dex-IIC [6137M]			
P/N 83 22 0 024 249	Dex-IID [GM 6137M]			
P/N 83 22 0 024 359	Dex-IIIE [GM 6137M]			
P/N 83 22 0 026 922	Dex-IIIF [GM 6297M]			
P/N 83 22 0 142 516	Dex-IIIG [GM 6417M]			
P/N 83 22 0 397 114	Dex-IIIH [GM N10055]			
P/N 83 22 0 402 413	Dex-HP*			
P/N 83 22 0 403 248/249	GMW 16444			
P/N 83 22 2 152 426	P/N 19 40 700			
P/N 83 22 2 163 514	P/N 19 40 767			
P/N 83 22 2 220 438/440	P/N 21005966			
P/N 83 22 2 220 442	P/N 88900925			
P/N 83 22 2 289 720	P/N 9986195 and P/N 9985010			
P/N 83 22 2 305 396	Saturn T-IV Fluid, Saturn P/N 22689186			
P/N 83 22 2 305 397	Type A Suffix A			
P/N 83 22 2 355 599	WS, P/N 88863400 / 88863401			
P/N 83 22 2 355 601	ATF DW-1 P/N 08200-9008			
P/N 83 22 2 413 477	ATF Type 3.0 P/N 08200-9016-A			
P/N 83 22 7 542 290	ATF Type 3.1 P/N 08200-9017			
P/N 83 22 9 407 765	ATF Z1, P/N 08200-9001			
P/N 83 22 9 407 807	ATF Z1, P/N 08200-9001A			
Bosch	Bosch TE-ML 09	Honda/Acura	ATF RED-1K	
			ATF SP-IV	
Citroen	Z 000169756			Genuine ATF
	D3-SP			JWS 3314
DAIHATSU	8 & 9 Speed ATF, P/N 68218925AA/AB			P/N 00232-19023
	ASRC			P/N 040000C90SG
	ATF+			P/N 04500-00140
	ATF+2			P/N UM040 CH20 Red-1
	ATF+3			SP
	ATF+4			SP4-M1
	AW-1, P/N 68092912AA			SPH-IV
	P/N 68043742AA			SP-II
	Fiat 9.55550-AV1			SP-III
	Fiat 9.55550-AV2		SP-IV	
Fiat 9.55550-AV4		SP-IV-RR		
			WS, spec NWS-9638	

* State of California does not approve this as suitable for use.

SERVICE PRO® GLOBAL FULL SYNTHETIC MULTI- VEHICLE ATF

Manufactured with highly refined base oils and industry leading additive chemistry

Service Pro Global Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:

OEM/ ATF	APPLICATION	OEM/ ATF	APPLICATION	
Isuzu	ATF II	Peugeot	P/N Z 000169756	
	ATF III		PSA 16 350 560 80	
	ATF WSI		JWS 3309, P/N 000 043 205 28	
	Genuine ATF		LT 71141	
	P/N 08200-9001		P/N 000 043 204 41	
Jaguar	SCS	Porsche	P/N 000 043 204 63	
	02JDE 26444		P/N 000 043 304 00/01	
	Fluid 8432		P/N 000 043 305 42	
	JLM 20238		P/N 000 043 305 43	
	JLM 20292		P/N 000 043 305 54	
	JLM 21044		P/N 000 043 306 24	
	K17, Jatco 3100 PL085		P/N 958 300 540 00	
	LT 71141		P/N 958 300 901 00	
JAMA	WSS-M2C922-A1	PSA	P/N 999 917 547 00 (A2) or P/N 000 043 205 09	
	JASO M315, Class 1-A		AL4 / 4HP20, P/N 9730AE	
Land Rover	JASO M315, Class 1-A-LV	Renault	B71 2340	
	ATF N402		DP-0	
	AW-1 P/N LR0022460: LV	Matic D2		
	JWS3309US	SATF-D		
MAN	P/N TYK500050	Rolls Royce	Oil No. PL 31493PA	
	339A		ATF HP	
	339D	Saab	JWS 3309	
	339F	P/N 93 160 393		
Maserati	LR023288/023289	Saturn	P/N 93 165 147	
	Oil No. 231603		Dex-III G	
Mazda	ATF A7	Ssangyong	T-IV Fluid, P/N 22689186	
	ATF FZ		DSIH 5M-52	
	ATF M-5 P/N 0000-23-ATF-M5	Subaru	DSIH 5M-66	
	ATF N-1		ATF HP, P/N K0140Y0700, P/N SOA635040	
	ATF S-1	ATF-WS		
	F-1	Suzuki	ATF 2326	
	JWS3317		ATF 2384K	
	M3		ATF 3314	
Type T-IV, JWS 3309 ATF	ATF 3317			
Mercedes	A 0019892203		Toyota	ATF 5D06
	ATF 3403-M115			Matic D
	Sheet 236.1	Matic J		
	Sheet 236.10	Matic S		
	Sheet 236.11	ATF FZ		
	Sheet 236.12	JWS 3309, Type T-IV, P/N 08886-81015		
	Sheet 236.14	JWS 3324, ATF WS (or NWS9638)		
	Sheet 236.15	Type D-II		
	Sheet 236.16	Type T		
	Sheet 236.17	Type T-II		
Sheet 236.2	Type T-III			
Sheet 236.41	Volvo	P/N 1161521		
Sheet 236.5		P/N 1161621		
Mini		P/N 1161640; P/N 1161540		
ATF JWS 3309, P/N 83 22 0 402 413		P/N 31 256 774, 31 256 775		
ATF-J2		P/N 31 492 172, 31 492 173		
ATF-J3	VW/Audi	G 052 162 (-A1, -A2) [AG4]		
Dia Queen ATF-MA1, P/N MZ320775		G 052 533		
Dia Queen ATF-PA, P/N 4030401		G 052 990 A2		
Dia Queen AW		G 053 001 A2		
DII/DIII		G 055 005 A2		
SP, P/N MS991156		G 055 025 (-A1, -A2)		
SP-II		G 055 162 A2 or A6		
SP-III		G 055 540 A2		
SP-IV		G 060 162 A2		
Fluid A		G 060 540 A2		
Matic D	G US 000 162			
Matic J, P/N 999MP-MTJ00P	ZF	LT 71141		
Matic K		LifeguardFluid 5 (ZF No. S671 090 170)		
Matic P, P/N 999MP-MTP10P		LifeguardFluid 6 (ZF No. S671 090 255)		
Matic R, P/N 999MP-MTR00P		LifeguardFluid 8 (ZF No. S671 090 312)		
Matic S, P/N 999MP-MTS00P		LifeguardFluid 9 (ZF No. AA01.500.001)		
Matic W	TE-ML 11A and TE-ML 11B			
N402	8 & 9 Speed ATF, P/N 68218925AA/AB			