

# SERVICE PRO® GLOBAL FULL SYNTHETIC MULTI-VEHICLE ATF

Manufactured with highly refined base oils and industry leading additive chemistry

**DESCRIPTION:**

SERVICE PRO® Global Full Synthetic Multi-Vehicle ATF represents the latest technology in full synthetic automatic transmission fluids. It is specifically formulated for the newest generation of high efficiency transmissions and is also a fuel efficient choice for older models as well.

SERVICE PRO® Global Full Synthetic Multi-Vehicle ATF meets the requirements of JASO M315-2013 1A-LV specification. Also suitable for use in many applications including many General Motors, Ford, FCA/Chrysler, Toyota/Lexus/ Scion (T-III, IV, WS), Nissan/Infiniti (Matic D, J, K, S, W), and Honda/Acura (ATF Z-1, DW-1) transmissions, as well as transmissions installed in Hyundai/ Kia (SP-II, III, IV, Red-1K), Isuzu (SCS, ATF II, III), Jaguar, Land Rover, Mazda(F-1, FZ, M-III, T-IV, MV), Mercedes-Benz (236.10, 236.3, 236.5, 236.6, 236.7, 236.9, 236.15), Mitsubishi (Diamond SP, II, III, ATF J2, J3), Porsche, BMW(LA2634, LT71141), MINI, SAAB, Subaru (HP), Suzuki, Volvo and VW/Audi (09A, 09G) cars and light trucks. It is also suitable for transfer case applications calling for Ford XL-12 fluid.

This product is NOT recommended for Ford Type F, Continuously Variable Transmissions (CVT) or Double Clutch Transmissions (DCT) which require specialized OEM fluids. Check owner’s manual for specific recommendations.

**PERFORMANCE BENEFITS:**

- Improved oxidation and thermal stability
- Full synthetic formula
- Outstanding low temperature performance
- Superior anti-wear protection
- Improved torque transfer

Note: This product is not for sale or use in the State of California.

**TYPICAL PROPERTIES\*:**

API Gravity	34.8
Sp. Gr. @ 60° F	0.8468
Flash. COC. ° F	400
Pour Pt.. ° F	-55
Viscosity. cP @ -40 °C	12100
Viscosity, cSt @ 40 °C	32
cSt @ 100 °C	6.3
Viscosity Index	152
Color	Red

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



## SERVICE PRO® GLOBAL FULL SYNTHETIC MULTI-VEHICLE ATF

Manufactured with highly refined base oils and industry leading additive chemistry

Service Pro Global Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:

OEM/ ATF	APPLICATION	OEM/ ATF	APPLICATION	
AISIN	AW-2	FCA continued	Fiat 9.55550-AV5	
	JWS 3309 ATF, ATF-0T4		Fiat 9.55550-AV6	
	JWS 3324 ATF, ATF-0WS		MB 236.10/12, P/N 05127382AA	
Allison	C2		P/N 05127382	
	C3		P/N 68157995AA/AB	
	C4		P/N 68333587AA	
ATF	134		SP-4, P/N 68171866AA	
	3353		SP-III	
	3100 PL085		SP-IV, P/N 68171866AA	
	3403-M115		SP-IV, P/N 68171869AA	
	D971	Type 7176E		
	ETL-7045 E	Type 9602		
	K17	ESP-M2C138-CJ		
	L12108	ESP-M2C166-H		
	LA 2634	P/N XT-10-QLV [LV], XT-10-QLVC		
	M-1375.4	P/N XT-12-ULV [ULV]		
	M-1375.6	P/N XT-2-QDX [M]		
	N402	P/N XT-2-QSM [Syn]		
	SP-III	P/N XT-5-QM [V]		
Bentley	P/N PY112995PA	Ford	P/N XT-5-QSM [V Syn]	
	ATF 3+		P/N XT-6-QSP [SP]	
ATF 7	P/N XT-8-QAW [Premium]			
ATF4	P/N XT-9-QMM5 [FNR5]			
ATF6	Spec WSS-M2C922-A1			
ETL-7045 and ETL-7045 E	ATF Z1, Saturn P/N 22717466			
ETL-8072B	AW-1, P/N 19256039			
LA 2634	Dex [GM 6032M]Dex ULV, P/N 19352619			
LT 71141	Dex-B [GM 6032M]			
M-L12108	Dex-III [6137M]			
BMW	P/N 81 22 9 400 272/275	GM	Dex-III [GM 6137M]	
	P/N 81 22 9 407 858/859		Dex-III [GM 6137M]	
	P/N 83 22 0 024 249		Dex-III [GM 6297M]	
	P/N 83 22 0 024 359		Dex-III [GM 6417M]	
	P/N 83 22 0 026 922		Dex-III [GM N10055]	
	P/N 83 22 0 142 516		Dex-HP*	
	P/N 83 22 0 397 114		Dex-VI [GMW 16444]	
	P/N 83 22 0 402 413		P/N 19 40 700	
	P/N 83 22 0 403 248/249		P/N 19 40 767	
	P/N 83 22 2 152 426		P/N 21005966	
	P/N 83 22 2 163 514	P/N 88900925		
	P/N 83 22 2 220 438/440	P/N 9986195 and P/N 9985010		
	P/N 83 22 2 220 442	Saturn T-IV Fluid, Saturn P/N 22689186		
	P/N 83 22 2 289 720	Type A Suffix A		
	P/N 83 22 2 305 396	WS, P/N 88863400 / 88863401		
	P/N 83 22 2 305 397	ATF DW-1 P/N 08200-9008		
	P/N 83 22 2 355 599	ATF Type 3.0 P/N 08200-9016-A		
	P/N 83 22 2 355 601	ATF Type 3.1 P/N 08200-9017		
	P/N 83 22 2 413 477	ATF Z1, P/N 08200-9001		
	P/N 83 22 7 542 290	ATF Z1, P/N 08200-9001A		
P/N 83 22 9 407 765	ATF RED-1K			
P/N 83 22 9 407 807	ATF SP-IV			
Bosch	Bosch TE-ML 09	Honda/Acura	Genuine ATF	
	Z 000169756		JWS 3314	
Citroen	D3-SP		Hyundai/Kia	P/N 00232-19023
	8 & 9 Speed ATF, P/N 68218925AA/AB			P/N 040000C90SG
ASRC	P/N 04500-00140			
ATF+	P/N UM040 CH20 Red-1			
ATF+2	SP			
ATF+3	SP4-M1			
ATF+4	SPH-IV			
AW-1, P/N 68092912AA	SP-II			
P/N 68043742AA	SP-III			
Fiat 9.55550-AV1	SP-IV			
Fiat 9.55550-AV2	SP-IV-RR			
Fiat 9.55550-AV4	WS, spec NWS-9638			

\* State of California does not approve this as suitable for use.

# SERVICE PRO® GLOBAL FULL SYNTHETIC MULTI-VEHICLE ATF

**Manufactured with highly refined base oils and industry leading additive chemistry**

**Service Pro Global Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:**

OEM/ ATF	APPLICATION	OEM/ ATF	APPLICATION	
Isuzu	ATF II	Peugeot	P/N Z.000169756	
	ATF III		PSA 16 350 560 80	
	ATF WSI	Porsche	JWS 3309, P/N 000 043 205 28	
	Genuine ATF		LT71141	
	P/N 08200-9001		P/N 000 043 204 41	
	SCS		P/N 000 043 204 63	
Jaguar	02JDE 26444		P/N 000 043 304 00/01	
	Fluid 8432		P/N 000 043 305 42	
	JLM 20238		P/N 000 043 305 43	
	JLM 20292		P/N 000 043 305 54	
	JLM 21044	P/N 000 043 306 24		
	K17, Jatco 3100 PL085	P/N 958 300 540 00		
JAMA	LT 71141	P/N 958 300 901 00		
	WSS-M2C922-A1	P/N 999 917 547 00 (A2) or P/N 000 043 205 09		
Land Rover	JASO M315, Class 1-A	PSA	AL4 / 4HP20, P/N 9730AE	
	JASO M315, Class 1-A-LV		B71 2340	
	ATF N402	Renault	DP-0	
	AW-1 P/N LR0022460: LV		Matic D2	
MAN	JWS3309US	Rolls Royce	SAIF-D	
	P/N TYK500050		Oil No. PL 31493PA	
	LR023288/023289	Saab	ATF HP	
Maserati	339A		JWS 3309	
	339D		P/N 93 160 393	
	339F	P/N 93 165 147		
Mazda	Oil No. 231603	Saturn	Dex-III G	
	ATF A7		T-IV Fluid, P/N 22689186	
	ATF FZ	Ssangyong	DSIH 5M-52	
	ATF M-5 P/N 0000-23-ATF -M5		DSIH 5M-66	
	ATF N-1	Subaru	ATF HP, P/N K0140Y0700, P/N SOA635040	
	ATF S-1		ATF-WS	
	F-1		ATF 2326	
	Mercedes	JWS3317	Suzuki	ATF 2384K
M3		ATF 3314		
Type T-IV, JWS 3309 ATF		ATF 3317		
A 0019892203		ATF 5D06		
ATF 3403-M115		Matic D		
Sheet 236.1		Matic J		
Sheet 236.10		Matic S		
Sheet 236.11		Toyota	ATF FZ	
Sheet 236.12			JWS 3309, Type T-IV, P/N 08886-81015	
Sheet 236.14			JWS 3324, ATF WS (or NWS9638)	
Sheet 236.15			Type D-II	
Sheet 236.16			Type T	
Sheet 236.17	Type T-II			
Sheet 236.2	Type T-III			
Sheet 236.41	Volvo	P/N 1161521		
Sheet 236.5		P/N 1161621		
ATF JWS 3309, P/N 83 22 0 402 413		P/N 1161640; P/N 1161540		
Mitsubishi	ATF-J2	VW/Audi	P/N 31 256 774, 31 256 775	
	ATF-J3		P/N 31 492 172, 31 492 173	
	Dia Queen ATF-MA1, P/N MZ320775		G 052 162 (-A1, -A2) [AG4]	
	Dia Queen ATF-PA, P/N 4030401		G 052 533	
	Dia Queen AW		G 052 990 A2	
	DII/DIII		G 053 001 A2	
	SP, P/N MS991156		G 055 005 A2	
	SP-II		G 055 025 (-A1, -A2)	
	SP-III		G 055 162 A2 or A6	
	SP-IV		G 055 540 A2	
Nissan	Fluid A		ZF	G 060 162 A2
	Matic D			G 060 540 A2
	Matic J, P/N 999MP-MTJ00P	G US 000 162		
	Matic K	LT71141		
	Matic P, P/N 999MP-MTP10P	LifeguardFluid 5 (ZF No. S671 090 170)		
	Matic R, P/N 999MP-MTR00P	LifeguardFluid 6 (ZF No. S671 090 255)		
	Matic S, P/N 999MP-MTS00P	LifeguardFluid 8 (ZF No. S671 090 312)		
	Matic W	LifeguardFluid 9 (ZF No. AA01.500.001)		
	N402	TE-ML 11A and TE-ML 11B		
		8 & 9 Speed ATF, P/N 68218925AA/AB		