

# **SERVICE PRO® PREMIUM FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID**

**Manufactured with highly refined base oils and industry leading additive chemistry  
FOR CALIFORNIA ONLY**

**DESCRIPTION:** SERVICE PRO® Premium Full Synthetic Automatic Transmission Fluid represents the latest technology in full synthetic automatic transmission fluids. It is specifically formulated for the newest generation of high efficiency transmissions and is a fuel efficient choice for older models as well.

**PERFORMANCE  
BENEFITS:**

- Improved oxidation and thermal stability
- Full synthetic formula
- Outstanding low temperature performance
- Superior anti-wear protection
- Improved torque transfer

SERVICE PRO® Premium Full Synthetic Automatic Transmission Fluid is designed for most conventional planetary gear transmission applications and meets JASO M315-2013, Class 1A-LV requirements.

This product is not recommended for Ford Type F, Continuously Variable Transmissions (CVT) or Dual Clutch Transmissions (DCT) which require specialized OEM fluids.

SERVICE PRO® Premium Full Synthetic Automatic Transmission Fluid has undergone extensive testing for a broad range of transmissions but is not an OEM licensed product. The respective vehicle manufacturers have not endorsed or evaluated Service Pro Premium Full Synthetic Automatic Transmission Fluid in these applications. If an OEM Licensed product is preferred, contact your local Service Pro Distributor about OEM Licensed Service Pro products.

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOOD Distributor if you require any further information.



Revised 04/2024 page 1  
SPFSATF

# SERVICE PRO® PREMIUM FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID

**Manufactured with highly refined base oils and industry leading additive chemistry  
FOR CALIFORNIA ONLY**

Suitable for use for the following applications:

OEM/ ATF	APPLICATION	OEM/ ATF	APPLICATION	
AISIN	AW-2	FCA continued	Fiat 9.55550-AV4	
	JWS 3309 ATF, ATF-OT4		Fiat 9.55550-AV5	
	JWS 3324 ATF, ATF-OWS		Fiat 9.55550-AV6	
Allison	C2		P/N 05127382	
	C3		P/N 68157995AA/AB	
	C4		P/N 68333587AA	
ATF	134		SP-4, P/N 68171866AA	
	3353		SP-III	
	3100 PLO85		SP-IV, P/N 68171866AA	
	3403-M115		SP-IV, P/N 68171869AA	
	D971		Type 7176E	
	ETL-7045 E		Type 9602	
	K17		Ford	P/N XT-9- QMM5 [FNR5]
	L12108			Spec WSS-M2C922-A1
	LA 2634			ATF Z1, Saturn P/N 22717466
	M-1375.4	AW-1, P/N 19256039		
	M-1375.6	Dex [GM 6032M]		
	N402	Dex-B [GM 6032M]		
SP-III	Dex-IIC [6137M]			
Bentley	P/N PY112995PA	Dex-IID [GM 6137M]		
		Dex-IIE [GM 6137M]		
BMW	ATF 3+	GM	Dex-IIIF [GM 6297M]	
	ATF 7		Dex-IIIG [GM 6417M]	
	ATF4		Dex-IIIH [GM N10055]	
	ATF6		Dex-VI [GMW 16444]	
	ETL-7045 and ETL-7045 E		P/N 19 40 700	
	ETL-8072B		P/N 19 40 767	
	LA 2634		P/N 21005966	
	LT 71141		P/N 88900925	
	M-L12108		P/N 9985010	
	P/N 81 22 9 400 272/275		P/N 9986195	
	P/N 81 22 9 407 858/859		Saturn T-IV Fluid, Saturn P/N 22689186	
	P/N 83 22 0 024 249		WS, P/N 88863400 / 88863401	
	P/N 83 22 0 024 359	Honda/Acura	ATF DW-1 P/N 08200-9008	
	P/N 83 22 0 026 922		ATF Type 3.0 P/N 08200-9016-A	
	P/N 83 22 0 142 516		ATF Type 3.1 P/N 08200-9017	
	P/N 83 22 0 397 114		ATF Z1, P/N 08200-9001	
	P/N 83 22 0 402 413		ATF Z1, P/N 08200-9001A	
	P/N 83 22 0 403 248/249		Hyundai/Kia	ATF RED-1K
	P/N 83 22 2 152 426	ATF SP-IV		
	P/N 83 22 2 163 514	Genuine ATF		
	P/N 83 22 2 220 438/440	JWS 3314		
	P/N 83 22 2 220 442	P/N 00232-19023		
	P/N 83 22 2 289 720	P/N 040000C90SG		
	P/N 83 22 2 305 396	P/N 04500-00140		
P/N 83 22 2 305 397	P/N UM040 CH20 Red-1			
P/N 83 22 2 355 599	SP			
P/N 83 22 2 355 601	SP4-M1			
P/N 83 22 7 542 290	SPH-IV			
P/N 83 22 9 407 765	SP-II			
P/N 83 22 9 407 807	SP-III			
Citroen	Z 000169756	SP-IV		
DAIHATSU	D3-SP	SP-IV-RR		
	8 & 9 Speed ATF, P/N 68218925AA/AB	WS, spec NWS-9638		
FCA	ASRC	Isuzu	ATF II	
	ATF+		ATF III	
	ATF+2		ATF WSI	
	AW-1, P/N 68092912AA		Genuine ATF	
	Dex-VI, P/N 68043742AA		P/N 08200-9001	
	Fiat 9.55550-AV1		SCS	
Fiat 9.55550-AV2				

# SERVICE PRO® PREMIUM FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID

**Manufactured with highly refined base oils and industry leading additive chemistry  
FOR CALIFORNIA ONLY**

Suitable for use for the following applications:

OEM/ ATF	APPLICATION	OEM/ ATF	APPLICATION	
<b>Jaguar</b>	O2JDE 26444	<b>Porsche</b>	P/N 000 043 204 63	
	Fluid 8432		P/N 000 043 304 00/01	
	JLM 20238		P/N 000 043 305 42	
	JLM 20292		P/N 000 043 305 43	
	JLM 21044		P/N 000 043 305 54	
	K17, Jatco 3100 PLO85		P/N 000 043 306 24	
	LT 71141		P/N 958 300 540 00	
	P/N 958 300 901 00			
<b>JAMA</b>	JASO M315, Class 1-A-LV			P/N 999 917 547 00 (A2) or P/N 000 043 205 09
<b>Land Rover</b>	ATF N402		<b>PSA</b>	AL4 / 4HP20, P/N 9730AE
	AW-1 P/N LR0022460: LV			B71 2340
	JWS3309US		<b>Renault</b>	DP-0
	P/N TYK500050			Matic D2
	LR023288/023289			SATF-D
<b>MAN</b>	339A	<b>Rolls Royce</b>	Oil No. PL 31493PA	
	339D		ATF HP	
	339F	<b>Saab</b>	JWS 3309	
<b>Maserati</b>	Oil No. 231603		P/N 93 160 393	
<b>Mazda</b>	ATF A7	<b>Saturn</b>	P/N 93 165 147	
	ATF FZ		Dex-III G	
	ATF M-5 P/N 0000-23-ATF -M5	<b>Ssangyong</b>	T-IV Fluid, P/N 22689186	
	ATF N-1		DSIH 5M-52	
	ATF S-1	<b>Subaru</b>	DSIH 5M-66	
	F-1		ATF HP, P/N K0140Y0700, P/N SOA635040	
	JWS3317		ATF-WS	
	M3	<b>Suzuki</b>	ATF 2326	
Type T-IV	ATF 2384K			
JWS 3309 ATF	ATF 3314			
	ATF 3317			
	ATF 5D06			
	Matic D			
<b>Mercedes</b>	A 0019892203	<b>Toyota</b>	Matic J	
	ATF 3403-M115		Matic S	
	Sheet 236.1		ATF FZ	
	Sheet 236.10		JWS 3309, Type T-IV, P/N 08886-81015	
	Sheet 236.11		JWS 3324, ATF WS (or NWS9638)	
Sheet 236.2	Type D-II			
Sheet 236.41	Type T			
Sheet 236.5	Type T-II and Type T-III			
<b>Mini</b>	ATF JWS 3309, P/N 83 22 0 402 413		<b>Volvo</b>	P/N 1161521
	ATF-J2			P/N 1161621
<b>Mitsubishi</b>	ATF-J3	P/N 1161640; P/N 1161540		
	Dia Queen ATF-MA1, P/N MZ320775	P/N 31 256 774, 31 256 775		
	Dia Queen ATF-PA, P/N 4030401	P/N 31 492 172, 31 492 173		
	Dia Queen AW	G 052 162 (-A1, -A2) [AG4]		
	DII/DIII	G 052 533		
	SP, P/N MS991156	G 052 990 A2		
	SP-II	G 053 001 A2		
	SP-III	G 055 005 A2		
SP-IV	G 055 025 (-A2)			
<b>Nissan</b>	Fluid A	<b>VW/Audi</b>	G 055 162 A2 or A6	
	Matic D		G 055 540 A2	
	Matic J, P/N 999MP-MTJOOP		G 060 162 A2	
	Matic K		G 060 540 A2	
	Matic P, P/N 999MP-MTP10P		G US 000 162	
	Matic R, P/N 999MP-MTR00P		LT 71141	
	Matic S, P/N 999MP-MTS00P			
	Matic W			
	N402			
<b>Peugeot</b>	P/N Z 000169756	<b>ZF</b>	LifeguardFluid 5 (ZF No. S671 090 170)	
	PSA 16 350 560 80		LifeguardFluid 6 (ZF No. S671 090 255)	
<b>Porsche</b>	JWS 3309, P/N 000 043 205 28		LifeguardFluid 8 (ZF No. S671 090 312)	
	LT 71141		LifeguardFluid 9 (ZF No. AA01.500.001)	
	P/N 000 043 204 41		TE-ML 11A and TE-ML 11B	
				8 & 9 Speed ATF, P/N 68218925AA/AB